LED ROADWAY LIGHTING
GE Area Lighter XL

NEW

The GE Area Lighter XL is a floodlight with a range of lumen packages and mounting configurations to best optimize area light applications, as well as providing versatility in lighting design within the same form-factor. Suitable for sporting arena's such as tennis/netball/basketball courts and Area lighting.

INTEGRATED SMART TECHNOLOGY

Applications
- Area lighting
- Sports Lighting

Electrical
- 350W-500W
- IP66 rated fitting
- System efficiency 150L m/w
- 20kV/10kA integral Surge Protection Device.

Controls
- 1-10V dimmable and Dali

LED & Optical Performance
- Asymmetrical and Symmetrical light distribution
- Lumen Output range 35000lm - 90000lm
- CCT 4000K @ 70 CRI
- Optional diffused lenses providing effective glare control

Mounting
- Standard and long trunnion arm option available allowing 360-degree rotation of luminaire

Finish
- Corrosion resistant polyester powder paint
- Standard colour is black (RAL9005)
- Custom colours available on request

Housing
- Net Weight 22.1kg - 23.5kg
- Standard LM6
- IK08 impact rated
- Sleek industrial design with a robust construction

CONNECTED LIGHT SOLUTIONS

Connected Light Solutions

Ph 1300 497 221 **Email** info@connectedlightsolutions.com.au connectedlightsolutions.com.au

LED ROADWAY LIGHTING
GE Area Lighter XL

Fixture dimensions (mm)

Model	product L * W * H (mm)	carton L * W * H (mm)	NW(kg)±0.3	GW(kg)±0.3
AREA350	690*708*94	800*800*150	22.1	24.7
AREA500			23	25.6

Product ID	Beam Angle	CCT	Wattage	Light Beam	LPW	Finish Colour	Socket Base	Dimming
ALXLU = Area Lighter XL	AS = Asymmetrical S = Symmetrical	N = 4000K	350 = 350W 500 = 500W	AWB = Asym. Wide Beam	H = 150lm/w	SG = RAL9007	0 = None 1 = Nema	A = Analogue D1 = Dali 1.0 D2 = Dali 2.0