


ETC340-GB LED

Inground luminaires

1/8

we-ef



Description

IP67. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Factory-sealed termination chamber with cable gland and 0.5 m of flexible PVC-free cable. Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC[®] One LED Concept. 20° tiltable and 355° rotatable. 1-10 V analogue dimming or DALI interface available on request. Luminaire installation blockout and sealable junction box included in supply. 2700 K option available on request. ASC Anti Slip Coating on request.

ETC340-GB LED


Inground luminaires

2/8

we-ef

Specifications

Material Specification

| | |
|---------------------|---|
| Body: | Stainless steel construction |
| Lens: | Safety glass lens, max. load 5 tonnes |
| Colours: |  Stainless Steel |
| Gasket: | Silicone rubber gasket |
| Fasteners: | PCS Polymer Coated Stainless Steel Hardware (unpainted) |
| Ingress protection: | IP67 |
| Impact protection: | IK10+ |

Electrical Specification

| | |
|-------------------|--|
| Power supply: | 230V / 50 Hz |
| Driver / Ballast: | Integral EC electronic converter |
| Termination: | Junction box supplied |
| Cable: | Complete with cable gland and 0.5 m of flexible PVC-free cable |

Warranty

The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.

ETC340-GB LED





Inground luminaires

3/8

we-ef

Choices

Light Distributions

| | |
|---|--|
|  | symmetric, wide beam [B] |
|  | symmetric, medium beam [M] |
|  | symmetric, very narrow beam [EE] |
|  | symmetric, very narrow beam, 'sharp cut-off' [EES] |

Nominal Lumen

2796

2951

4440

Nominal Watt

24

36

Colour Temperatures

2700 K

3000 K

4000 K

Colours

Stainless Steel





ETC340-GB LED

Inground luminaires

4/8

we-ef

Configurations

| Light Distributions | Part ID | Light Source | Delivered Lumens | Rated Input Power | CRI | Weight | Link |
|--|----------|------------------------------|------------------|-------------------|-----|--------|---------------------|
|  symmetric, wide beam [B] | 185-7820 | LED-12/24W / 700 mA - 2700 K | 2113.8 | 28 | 80 | 12.00 | 📄 ↗ |
| | 185-7713 | LED-12/24W / 700 mA - 3000 K | 2231 | 28 | 80 | 12.00 | 📄 ↗ |
| | 185-7715 | LED-12/24W / 700 mA - 4000 K | 2231 | 28 | 80 | 12.00 | 📄 ↗ |
|  symmetric, medium beam [M] | 185-7821 | LED-12/24W / 700 mA - 2700 K | 2426.9 | 28 | 80 | 12.00 | 📄 ↗ |
| | 185-9722 | LED-12/24W / 700 mA - 3000 K | 2560.6 | 28 | 80 | 12.00 | 📄 ↗ |
| | 185-9726 | LED-12/24W / 700 mA - 4000 K | 2560.6 | 28 | 80 | 12.00 | 📄 ↗ |
|  symmetric, very narrow beam [EE] | 185-7822 | LED-12/24W / 700 mA - 2700 K | 2289.9 | 28 | 80 | 12.00 | 📄 ↗ |
| | 185-9721 | LED-12/24W / 700 mA - 3000 K | 2417.3 | 28 | 80 | 12.00 | 📄 ↗ |
| | 185-9725 | LED-12/24W / 700 mA - 4000 K | 2417.3 | 28 | 80 | 12.00 | 📄 ↗ |
|  symmetric, very narrow beam, 'sharp cut-off' [EES] | 185-7823 | LED-12/24W / 700 mA - 2700 K | 2438.1 | 28 | 80 | 12.00 | 📄 ↗ |
| | 185-7714 | LED-12/24W / 700 mA - 3000 K | 2572 | 28 | 80 | 12.00 | 📄 ↗ |
| | 185-7716 | LED-12/24W / 700 mA - 4000 K | 2572 | 28 | 80 | 12.00 | 📄 ↗ |

Related Families / ETC300-GB

| Family | | Dimensions | Wattage | Nominal Lumen | Links | |
|---------------|---|------------|----------|---------------|---------------------|---------------------|
| | | | | | Links | Download Data Sheet |
| ETC320-GB LED | ⊙ | 160 | 6 W | 738 | 📄 ↗ | 📄 ↓ |
| ETC330-GB LED | ⊙ | 250 | 12 W | 1476 | 📄 ↗ | 📄 ↓ |
| ETC340-GB LED | ⊙ | 300 | 24 -36 W | 2796 -4440 | 📄 ↗ | 📄 ↓ |

ETC340-GB LED

Inground luminaires


5/8

we-ef

Mounting Accessories

Installation cover


185-0326 Installation cover BE



Optical Accessories

Colour filter

on request Colour filter IF



Surface wash lens


ETC340-GB LED

Inground luminaires

6/8

we-ef

185-7582 Flood lens IO-360



C1

ETC340-GB LED

Inground luminaires

7/8

we-ef


Linear louvre

■ **185-9568** Linear louvre IL



Linear spread lens

■ **185-7581** Linear spread lens IO



ETC340-GB LED


Inground luminaires

8/8

we-ef

Optical Adaptor

■ **185-7419** Internal optical Adaptor



Control

1-10 V analogue dimming interface

■ **430-0011** 1-10 V analogue dimming

DALI interface

■ **430-0013** DALI interface