



STANDING DATA FOR MSATS

PREPARED BY: AEMO Markets
VERSION: 4.32
EFFECTIVE DATE: 01 December 2017
STATUS: DRAFT

Formatted: Font: 9 pt



Australian Energy Market Operator Ltd ABN 94 072 010 327 www.aemo.com.au info@aemo.com.au
NEW SOUTH WALES QUEENSLAND SOUTH AUSTRALIA VICTORIA AUSTRALIAN CAPITAL TERRITORY TASMANIA WESTERN AUSTRALIA

Australian Energy Market Operator Ltd ABN 94 072 010 327 www.aemo.com.au info@aemo.com.au
NE Australian Energy Market Operator Ltd ABN 94 072 010 327 www.aemo.com.au info@aemo.com.au
NEW SOUTH WALES QUEENSLAND SOUTH AUSTRALIA VICTORIA AUSTRALIAN CAPITAL TERRITORY TASMANIA

VERSION RELEASE HISTORY

Version	Effective Date	Summary of Changes
1.0	3/10/01	Initial Version
1.1	9/10/01	Title of document amended to Standing Data for MSATS, explanatory notes added, other editorial changes.
2.0	22/04/02	Document amended for Release 2 (Change Request 159)
2.1	2/5/02	Further minor changes prior to issue for MSATS Release 2.
2.2	7/5/02	Further minor changes prior to issue for MSATS Release 2.
2.3	12/8/02	Further minor changes to clarify, update, and correct data details for MSATS Release 2.
2.4	14/10/02	Further minor changes to clarify, update, and correct data details for MSATS Release 2.
2.5	11/07/2003	NMI Participant Relations table was included and minor updates and corrections were made
2.6	12/09/2005	Added clarification on definition of SerialNumber.
3.0	20/10/2006	Updated the tables in sections 43 to 109 by replacing the MSATS field details with the aseXML ones and removing the customer transfer column. The new sections are: additional reference tables (section 1110); the use of the NMI Suffix field (section 1211); examples of the assignment of data for different metering installations (sections 1312 to 1514); cross reference table of Browser screen fields and aseXML data elements (section 1615); examples of typical field values different types of Connection Points (section 1716); definitions of the data types used in sections 43 to 109 (section 1817); and a glossary 18.
3.1	16/06/2009	Minor updates and typographical corrections.
4.0	Aug 2009	Update to AEMO Format
4.1	19/04/2012	Updates to NMI Data tables to include Feeder Class, Customer Classification Code & Customer Threshold Code and minor data corrections.
4.2	28/08/2013	Updated wording for Nx suffixes in sections 87, 98 and 124. Updated reference to the CATS procedures for Embedded Networks in section 76. Added new data stream type codes under section 110: Reference Tables. Updated reference to the NEM Metrology Procedures in section 154 & 48.
4.3	01 December 2017	Updated to incorporate: <ul style="list-style-type: none"> • National Electricity Amendment (Expanding competition in metering and related services) Rule 2015 No. 12; • National Electricity Amendment (Embedded Networks) Rule 2015 No. 15; and • National Electricity Amendment (Meter Replacement Processes) Rule 2016 No. 2.

Formatted Table

Formatted: Indent: Left: 0 cm, Hanging: 0.7 cm, Bulleted + Level: 1 + Aligned at: 0 cm + Indent at: 1.27 cm

CONTENTS

1. INTRODUCTION	4
1.1. Purpose and scope	4
1.2. Definitions and interpretation	4
1.3. Related documents	4
2. BACKGROUND	4
3. CONVENTIONS USED WITHIN THIS DOCUMENT	5
3.1. Column Headed: Standing Data Required	5
3.2. NMIs Affected	5
4. CATS METER REGISTER	6
5. CATS DLF CODES	11
6. CATS EMB NET ID CODES	11
7. CATS NMI DATA	12
8. CATS NMI DATA STREAM	15
9. CATS REGISTER IDENTIFIER	1817
10. CATS NMI PARTICIPANT RELATIONS	2219
11. REFERENCE TABLES	2320
12. USE OF NMI SUFFIX TO POPULATE CATS REGISTER IDENTIFIER	2521
13. ASSIGNMENT OF DATA – ACCUMULATION METERS	2622
13.1. Single Meter, no controlled load	2622
13.2. Two Single Element Meters, no controlled load	2723
13.3. Two Single Element Meters, one with controlled load	2723
13.4. One Meter with Two Registers, one measuring a controlled load	2723
13.5. Single Multi-function Meter	2824
13.6. Two meters, three registers. One register measures a controlled load	2824
14. ASSIGNMENT OF DATA – INTERVAL METERS	2925
14.1. One meter	2925
14.2. Import/Export meter	2925
14.3. One meter: multiple registers	3026
14.4. One meter: Twin Measurement Elements	3026
15. ASSIGNMENTS OF DATA – SAMPLE METERS	3227
15.1. Multifunction Sample Meter	3228
16. CROSS REFERENCE OF BROWSER AND ASEXML DATA ELEMENTS	3228
17. EXAMPLES OF TYPICAL FIELD VALUES	4136
18. DATA TYPE CONVENTIONS	4741

1. INTRODUCTION

1.1. Purpose and scope

This document details the data requirements for the various data elements comprising the CATS NMI Standing Data stored for each NMI, together with relevant examples and definitions.

1.2. Definitions and interpretation

The Retail Electricity Market Procedures – Glossary and Framework:

- (a) is incorporated into and forms part of this document; and
- (b) should be read with this document.

1.3. Related documents

Title	Location
<u>Retail Electricity Market Procedures – Glossary and Framework</u>	http://aemo.com.au/Electricity/National-Electricity-Market-NEM/Retail-and-metering/Glossary-and-Framework
<u>CATS Procedures</u>	http://www.aemo.com.au/Electricity/National-Electricity-Market-NEM/Retail-and-metering/Market-Settlement-and-Transfer-Solutions
<u>WIGS Procedures</u>	http://www.aemo.com.au/Electricity/National-Electricity-Market-NEM/Retail-and-metering/Market-Settlement-and-Transfer-Solutions
<u>MDM Procedures</u>	http://www.aemo.com.au/Electricity/National-Electricity-Market-NEM/Retail-and-metering/Market-Settlement-and-Transfer-Solutions
<u>MSATS CATS history Model</u>	http://www.aemo.com.au/Electricity/National-Electricity-Market-NEM/Retail-and-metering/Market-Settlement-and-Transfer-Solutions
<u>MSATS guides</u>	http://www.aemo.com.au/Electricity/National-Electricity-Market-NEM/Retail-and-metering/Market-Settlement-and-Transfer-Solutions

2. BACKGROUND

The five MSATS master tables are contain the standing data stored for each NMI. They are the following:

Table 1 MSATS Master Tables

Table	Summary of Contents
CATS_NMI_DATA	Address, TNI <u>Code</u> , DLF <u>Code</u> , aggregate flag, embedded network names, Jurisdiction, NMI status <u>code</u> , etc
CATS_NMI_PARTICIPANT_RELATIONS	Roles and associated Participants. Separate records are maintained for each Role-/Participant relationship.
CATS_NMI_DATA_STREAM	Suffix, ADL <u>Code</u> , Profile Name, Datastream type and datastream status of each MDM Datastream.
CATS_METER_REGISTER	Meter Serial <u>ID</u> , meter type, meter manufacturer, test results, etc
CATS_REGISTER_IDENTIFIER	Meter Serial <u>ID</u> , Network Tariff Code, unit of measure etc

These are the five key master tables that contain the standing data stored for each NMI.

For a NMI to be capable of being used exist in MSATS, it must have the following minimum set of data:

- At least one record on the CATS_NMI_DATA table; and

- At least eight records on the CATS_NMI_PARTICIPANT_RELATIONS table, one for each of the mandatory roles (ROLR, LNSP, LR, RP, FRMP, MDP, MPC and MPB).

It will also normally have:

- At least one record on each of the CATS_METER_REGISTER and CATS_REGISTER_IDENTIFIER (there should be at least one record for each *meter* and register associated with the *NMI*) tables.

NMIs may or may not have:

- Records on the CATS_NMI_DATA_STREAM table. If *metering data* is to be submitted to the [Metering Data Management system \(MDM\)](#) there must be at least one valid record on this table.

Every time a change is made to any of the data in any of these tables, the old records are made inactive and new records are created, thus ensuring that there is a complete history of all changes.

2.3. CONVENTIONS USED WITHIN THIS DOCUMENT

The format of the [various](#) data fields indicated in the [Browser Format Column 'Data Type'](#) column of the [following](#) [Tables](#) is as defined in section 187.

The following information defines the coded entries in columns used in the [Tables 3 - 9](#) in sections 43 to 109.

2.3.1. Column Headed: Standing Data Required

The column indicates the requirement to provide this data to MSATS.

Table 2 Explanation of Standing Data Requirements

Requirement	Description
MANDATORY	Transfer, Validation or processing cannot proceed without this data.
REQUIRED	This data must be provided if this information is available.
OPTIONAL	This data is not required, but will be accepted if delivered.
Address Option 1	AEMO's preferred address option. If the applicable fields labelled "Address Option 1" cannot be provided, "Address Option 2" is MANDATORY.
Address Option 2	AEMO's non-preferred address option. If Address Option 1 is provided, these fields are not to be supplied.

2.3.2. NMIs Affected

Data must be provided for every *NMI* ~~which must be registered~~ in MSATS. The *NMIs* that must be registered in MSATS are:

- Every ~~*NMI* eligible for contestability in Victoria, NSW, ACT and South Australia. Include other Jurisdictions when FRC is introduced and NMI discovery provided by MSATS.~~
- Every ~~First Tier NMI and~~ Second Tier NMI ~~in Queensland and Tasmania~~ in the *NEM*.
- Sample *meters* for non-NSLP profile calculations and *embedded generat*~~ing~~ *units* for NSLP calculations.
- Every wholesale *connection point* in the *NEM*, including ~~generators~~*generation*, *interconnectors* and bulk *supply* points.

Formatted: Caption Table

Formatted Table

3.4. CATS_METER_REGISTER

The CATS_Meter_Register table is a NMI master table containing data that is stored at the Meter Register level. Information stored at this level includes the [Next Scheduled Read Date NSRD](#). It is updated whenever a Change Request containing inbound Meter Register data is completed.

Note: References to 'LNSP' includes the ENM for child connection points.

Table 3 CATS METER REGISTER

Data Element Name	Description	Standing Data Required	Party to Provide Required to Source	Rules Schedule 7.5NER Reference / Description
AdditionalSiteInformation	Free text, descriptive information in relation to the Site, which describes Site access and the relationship between the <i>metering point</i> and the <i>connection point</i> .	OPTIONAL	Metering Provider "B" MPB	S7.5.2(a)(3) Site identification names
AssetManagementPlan	Asset management plan If a Site plan is used, free text description of plan. If a sample plan is used, the name of the AEMO approved plan.	OPTIONAL	MPB Metering Provider "B"	S7.5.2(b)(6) Asset management plan and testing schedule
CalibrationTables	Calibration tables – details of any calibration factors programmed into the <i>meter</i> .	OPTIONAL	MPB Metering Provider "B"	S7.5.2(b)(7) Calibration tables, where applied to achieve <i>metering installation</i> accuracy
CommunicationsEquipmentType	Used to store baud rate for installed communication equipment in a code, calculated by dividing the baud rate by 100, of the installed communication equipment. For example, 48 = 4800 baud.	OPTIONAL	MPB Metering Provider "B"	S7.5.2(c)(2) Communication equipment type and serial numbers
CommunicationsProtocol	Used to provide details of access through switch units (if installed). Data to include Switch Unit, Dial Pkg, Port#, userid, password.	OPTIONAL	MPB Metering Provider "B"	S7.5.2(c)(3) Communication protocol details or references
DataConversion	Actual Pulse Multipliers	OPTIONAL	MPB Metering Provider "B"	S7.5.2(c)(4) Data conversion details
DataValidations	Free text description of required data validations.	OPTIONAL	MPB Metering Provider "B"	<ul style="list-style-type: none"> S7.5.2(d)(1) Algorithms S7.5.2(d)(2) Data comparison techniques S7.5.2(d)(3) Processing and alarms (eg. voltage

STANDING DATA FOR MSATS



				source limits; phase-angle limits) <ul style="list-style-type: none"> • S7.5.2(d)(5) Check metering S7.5.2(d)(4) compensation details • Alternative data sources
EstimationInstructions	Estimation instructions. Free text field	OPTIONAL	MPBMetering Provider "B"	
LastTestDate	The date on which the metering installation was last tested or inspected by the Metering Provider "B". This date will be used if Rules clause 7.9.45(a) of the NER needs to be applied.	OPTIONAL	MPBMetering Provider "B"	S7.5.2(b)(5) Test results and references to test certificates
MeasurementType	Code based on the <i>NMI</i> suffix codes, indicating the type of measurements available from the <i>meter</i> . For example, EBQK = bidirectional <i>energy</i> plus reactive Interval Meter.	OPTIONAL NOT USED for types 6 & 7 Customer Transfers.	MPBMetering Provider "B"	
Constant	The <i>meter</i> K_E (intrinsic constraint of meter in Wh/pulse).	OPTIONAL	MPBMetering Provider "B"	S7.5.2(b)(9) Summation scheme values and multipliers
Hazard	Free text or code which identifies hazards associated with reading the <i>meter</i> .	OPTIONAL	MPBMetering Provider "B" Responsible Person	S7.5.2(a)(1) Agreed location and reference details (eg drawing numbers)
InstallationTypeCode	The Metering Installation Type Code indicates whether or not the metering installation has to be manually read. This value must correspond to a valid MeterInstallCode value in the Meter Installation Codes reference table listed in section 11.40 .	MANDATORY	MPBMetering Provider "B"	S7.5.2(b)(3) Metering installation types and models
Location	Free text descriptive material which identifies the relationship between the location of the <i>metering point</i> and the <i>connection point</i> .	OPTIONAL	MPBMetering Provider "B"	S7.5.2(a)(1) Agreed location and reference details (eg drawing numbers)
Manufacturer	Free text field to identify the manufacturer of the installed <i>meter</i> .	OPTIONAL	MPBMetering Provider "B"	S7.5.2(b)(3) <i>Metering installation</i> types and models
Model	Free text field to identify the <i>meter</i> manufacturer's designation for the <i>meter</i> model.	OPTIONAL	MPBMetering Provider "B"	S7.5.2(b)(3)

STANDING DATA FOR MSATS



				Metering installation types and models
Point	Identifies the <i>meter</i> uniquely for the <i>NMI</i> . In the format 0n, where n is the <i>meter</i> number per the protocol described in the NMI Procedure. The allowed values are 01 to 09, 0A to 0H, 0J to 0N, 0P to 0Z. This will allow an audit trail when one <i>meter</i> is removed and a new <i>meter</i> is given the same MeterPoint value.	OPTIONAL	MPBMetering Provider "B"	
Program	Free text field providing a description of the program used to initialise the installed <i>meter</i> .	OPTIONAL	MPBMetering Provider "B"	
ReadTypeCode	Code to denote the method and frequency of Meter Reading. 1. First Character = Remote (R) or Manual (M); 2. Second Character = Mode T = telephone W = wireless P = powerline I = infra-red G = galvanic V = visual 3. Third Character = Frequency of Scheduled Meter Readings 1 = Twelve times per year 2 = Six times per year 3 = Four times per year D = Daily or weekly 4. Fourth Character = Undefined. For example, MV3 = Manual, Visual, Quarterly.	OPTIONAL	MPBMetering Provider "B"	
Route	The route identifier the <i>meter</i> is currently being read in.	OPTIONAL	MPBMetering Provider "B"	
SerialNumber	The Meter Serial number-ID uniquely identifies a <i>meter</i> for a given <i>NMI</i> . Maximum 12 Characters (alpha numeric). Unique for <i>NMI</i> . Use dummy for UMCP (Type 7) and logical (meters). Except for UMCP and logical, SerialNumber should be as displayed on the physical device (also known as property number). SerialNumber to be property number if exists, otherwise the <i>meter</i> manufacturer's serial number, otherwise dummy number.	MANDATORY	MPBMetering Provider "B"	S7.5.2(b)(1) Meter Serial numbersIDs
Status	A code to denote the status of the <i>meter</i> within the NEM . This value must correspond to a valid ElectricityMeter/Status in the Meter and RegisterID Codes reference table listed in section 1149 .	MANDATORY	MPBMetering Provider "B"	See section 4.11.3 of the CATS Procedures CATS Rules

STANDING DATA FOR MSATS



Use	A code identifying how the <i>meter</i> is used within the NEM .	OPTIONAL	MPBMetering Provider "B"	
NextScheduledReadDate	Indicates the Scheduled Next Read Date for the <i>meter</i> if a manual Meter Reading is required.	OPTIONAL	MPB Metering Provider "B" initially, then MDP for updates	
NextTestDate	Next date on which the <i>meter</i> should be tested.	OPTIONAL	MPBMetering Provider "B"	
NMI	National Metering Identifier issued by the LNSP in accordance with the NMI Procedure NMI. This number is unique for each <i>connection point</i> within the <i>NEM</i> .	MANDATORY	LNSP	S7.5.2(b)(2) <i>Metering installation</i> identification name
Password	Read & time set passwords separated by a space.	OPTIONAL	MPBMetering Provider "B"	S7.5.2(c)(6) 'write' password to be managed outside MSATS
RemotePhoneNumber	The PSTN-public telephone number to contact a remote Site for <i>metering data</i> . Includes STD prefix and no spaces.	OPTIONAL	MPB Metering Provider "B"	S7.5.2(c)(1) Telephone number(s) for access to data
TestCalibrationProgram	Test & calibration program.	OPTIONAL	MPBMetering Provider "B"	S7.5.2(b)(5) Current test and calibration program details
TestPerformedBy	Identifying the Metering Provider "B" and the technician responsible for conducting the last test. The technician is not to be named, but is to be identified by a number unique to the Metering Provider "B".	OPTIONAL	MPBMetering Provider "B"	S7.5.2(b)(5) Test results and references to test certificates
TestResultAccuracy	The accuracy figure from the test performed on the date indicated in the LastTestDate field.	OPTIONAL	MPBMetering Provider "B"	
TestResultNotes	A statement of compliance indicating the standard of the test regime applied at the time of the last test.	OPTIONAL	MPBMetering Provider "B"	S7.5.2(b)(5) Test results and references to test certificates
TransformerLocation	A free text field to identify the existence of instrument transformers and their location relative to the market connection point.	OPTIONAL	MPBMetering Provider "B"	S7.5.2(a)(1) Agreed location and reference details (eg drawing numbers)
TransformerRatio	A statement of the available and applied <i>transformer ratios</i> .	OPTIONAL	MPBMetering Provider "B"	S7.5.2(b)(4) Instrument <i>transformer ratios</i> (available and connected)

STANDING DATA FOR MSATS



TransformerType	An explanation of the type of <i>transformation</i> used.	OPTIONAL	MPBMetering Provider "B"	S7.5.2(b)(3) <i>Metering installation types and models</i>
UserAccessRights	Details of any End User consumer access to the <i>metering installation</i> ; examples include pulse outputs, interface to consumer load management system, or consumer directly accessing data in <i>meter</i> by special agreement.	OPTIONAL	MPBMetering Provider "B"	S7.5.2(c)(5) User access rights
FromDate	Start date of the record. This indicates the date on which the parameters of this particular record apply from. The data applies from the beginning of this date (the start of the day, i.e. 00:00).	MANDATORY	Participant sending transaction	
ToDate	End date of the record. This indicates the date on which the parameters of this particular record end. The data applies until the end of this date (the end of the day, i.e. 23:59). A default date of 9999-12-31 is recorded if EndDate is not provided.	MANDATORY (Defaults to high date unless supplied)	System generated unless supplied.	
RowStatus	Indicates whether the record is active or inactive. Whenever a new record is created, it will be A (Active). When, because there has been a change to the data, will make this record becomes redundant, and its MaintActFlg is changed to I (Inactive).	MANDATORY	System generated	
MaintenanceDate	Date and time the record was updated. A default date of 9999-12-31 is used when the record is created initially. If the record is subsequently updated, its MaintUpdDt is changed to the date and time the record was updated.	MANDATORY	System generated	
CreationDate	Date and time the record was created.	MANDATORY	System generated	

4.5. CATS_DLF_CODES

The CATS_DLF_Codes table contains a list of [distribution loss factor DLF Codes](#) and their relevant values. The StartDate and DLFCode fields will need to be provided for [settlements](#) calculations.

Note: References to 'LNSP' includes the ENM for child connection points.

Table 4 CATS_DLF_CODES

Formatted: Caption Table, Space Before: 0 pt

Data Element Name	Description	Standing Data Required	Party to Provide Required to Source
DistributionLossFactor Code	A four character alpha-numeric code used to identify DLF values. Complies with nationally established rules. All NMI/s in the system must be assigned a DLF Code. Refer to AEMO Distribution Loss Factor documents for each financial year, document no MT_GN1707v00x.	MANDATORY	AEMO\LNSP (AEMO updates MSATS)
DistributionLossFactor Description	Description of the DLF Code and value.	MANDATORY	AEMO\LNSP (AEMO updates MSATS)
DistributionLossFactor Value	Numeric value up to 5 decimal places, reflecting the value of the DLF Code.	MANDATORY	AEMO\LNSP (AEMO updates MSATS)
JurisdictionCode	Jurisdiction code to which the NMI belongs. This value must correspond to a valid JurisdictionCode in the Jurisdiction Codes reference table listed in section 1140 .	MANDATORY	AEMO\LNSP (AEMO updates MSATS)
RowStatus	Indicates whether the DLF Code is active or inactive. Whenever a new record is created, it will be A (Active). When, because there has been a change to the data, this record becomes redundant, its MaintActFlg is changed to I (Inactive).	MANDATORY	System generated
FromDate	Start date of the record. This indicates the date on which the parameters of this particular record apply from. The data applies from the beginning of this date (the start of the day, i.e. 00:00).	MANDATORY	AEMO\LNSP (AEMO updates MSATS)
ToDate	End date of the record. This indicates the date on which the parameters of this particular record end. The data applies until the end of this date (the end of the day, i.e. 23:59). A default date of 9999-12-31 is recorded if EndDate is not provided.	MANDATORY	System generated
MaintenanceDate	Date and time the record was updated. A default date of 9999-12-31 is used when the record is created initially. If the record is subsequently updated, its MaintUpdtDt is changed to the date and time the record was updated.	MANDATORY	System generated
CreationDate	Date and time the record was created.	MANDATORY	System generated

5.6. CATS_EMB_NET_ID_CODES

The CATS_EMBmb_NETet_ID_CODECodes table contains embedded network identifier codes, which are used to identify which *embedded network* a *NMI* belongs to, either as a Parent [NMI](#) or a Child [NMI](#).

Note: References to 'LNSP' includes the ENM for *child connection points*.

Table 5 CATS EMB NET ID CODES

Data Element Name	Description	Standing Data Required	Party Required To Source or Provide
EmbeddedNetwork Identifier	Embedded Network Code for embedded network identifier. Refer to Allocation of Embedded Network Codes (Document No. MT_GN1710) for further details.	MANDATORY	AEMO\NSP (AEMO updates MSATS)
EmbeddedNetwork Description	Description of embedded network identifier.	MANDATORY	AEMO\NSP (AEMO updates MSATS)
SuburbOrPlaceOrLocality	Locality to which the embedded network identifier belongs.	MANDATORY	AEMO\NSP (AEMO updates MSATS)
PostCode	Postcode for the locality to which the embedded network identifier belongs.	MANDATORY	AEMO\NSP (AEMO updates MSATS)
StateOrTerritory	Defined State or Territory abbreviation per in accordance with AS_4590.	MANDATORY	AEMO\NSP (AEMO updates MSATS)
RowStatus	Indicates whether the code is active or inactive. Whenever a new record is created, it will be A (Active). When, because there has been a change to the data, this record becomes redundant, its MaintActFlg is changed to I (Inactive).	MANDATORY	System generated
FromDate	Start date of the record. This indicates the date on which the parameters of this particular record apply from. The data applies from the beginning of this date (the start of the day, i.e. 00:00).	MANDATORY	AEMO\NSP (AEMO updates MSATS)
ToDate	End date of the record. This indicates the date on which the parameters of this particular record end. The data applies until the end of this date (the end of the day, i.e. 23:59). A default date of 9999-12-31 is recorded if EndDate is not provided.	MANDATORY	System generated
MaintenanceDate	Date and time the record was updated. A default date of 9999-12-31 is used when the record is created initially. If the record is subsequently updated, its MaintUpdtDt is changed to the date and time the record was updated.	MANDATORY	System generated
CreationDate	Date and time the record was created.	MANDATORY	System generated

6-7. CATS_NMI_DATA

The CATS_NMI_DATA table records Master NMI ~~Record~~ data information. It is updated whenever a Change Request containing ~~data in the CATS_INBOUND_NMI_DATA table inbound NMI Data~~ is completed.

Note: The LR / ENLR is the party required to source the data in the case of an embedded network Child NMI.

Note: References to 'LNSP' includes the ENM for *child connection points*.

Table 6 CATS NMI DATA

Data Element Name	Description	Standing Data Required	Party to Provide Required To Source
NMI	Unique National Metering Identifier (NMI) . All alpha characters are Upper Case	MANDATORY	LNSP See note above
NMI ClassificationCode	Code used to indicate the NMI Classification Code of this NMI. This value must correspond to a valid NMIClassCode value in the NMI Class Codes reference table listed in section 11.40 .	MANDATORY	LNSP See note above
MasterData/StatusCode	Code used to indicate the status of the NMI. This value must correspond to a valid MasterData/Status value in the NMI Status Codes reference table listed in section 11.40 .	MANDATORY	LNSP See note above
TransmissionNodeIdentifier	This value must correspond to a valid code in the CATS_TNI_Codes table.	MANDATORY	LNSP See note above
JurisdictionCode	Jurisdiction code to which the NMI belongs. This code defines the jurisdictional rules which apply to the transfer of this NMI. This value must correspond to a valid JurisdictionCode value in the Jurisdiction Codes reference table listed in section 11.40 .	MANDATORY	LNSP See note above
DistributionLossFactorCode	Distribution Loss Factor Code. Must be a valid code in the CATS_DLF_Codes table.	MANDATORY	LNSP See note above
ChildEmbeddedNetworkIdentifier	The embedded network identifier code is used to identify which embedded network this given NMI is the 'child of'. (If on a NMI record this field is not populated, it is assumed the NMI is not the child of any other NMI.) Must be a valid code within the CATS_Emb_Net_ID_Codes table. This field cannot be used unless the Parent NMI has been created and assigned an embedded network identifier code. Refer CATS Procedure section 30.4.4.a of the CATS Procedure .	REQUIRED	LNSP See note above
ParentEmbeddedNetworkIdentifier	The embedded network identifier code is used to identify which <i>embedded network</i> this given NMI is the 'parent of'. (If on a NMI record this field is not populated, it is assumed the NMI is not the parent of any other NMI.) Must be a valid code within the CATS_Emb_Net_ID_Codes table.	REQUIRED	LNSP See note above
BuildingOrPropertyName	A free text description of the full name used to identify the physical building or property as part of its location.	Address Option 1	LNSP See note above
LotNumber	The lot reference number allocated to an address prior to street numbering. The word 'LOT' is not required.	Address Option 1	LNSP See note above
FlatOrUnitNumber	Specification of the number of the flat or unit which is a separately identifiable portion within a building/complex.	Address Option 1	LNSP See note above
FlatOrUnitType	Specification of the type of flat or unit which is a separately identifiable portion within a building/complex. This value must correspond to a valid Flat Type Code, reference AS4590.	Address Option 1	LNSP See note above

FloorOrLevelNumber	Floor Number is used to identify the floor or level of a multi-storey building/complex.	Address Option 1	LNSP See note above
FloorOrLevelType	Floor Type is used to identify the floor or level of a multi-storey building/complex. This value must correspond to a valid Floor Type Code in the Floor Type Codes, reference AS4590.	Address Option 1	LNSP See note above
HouseNumber	The numeric reference of a house or property. Specifically the house number.	Address Option 1	LNSP See note above
HouseNumberSuffix	The numeric reference of a house or property. Specifically the single character identifying the house number suffix.	Address Option 1	LNSP See note above
StreetName	Records the thoroughfare name. See notes at end of table for more information on Structured Addresses	Address Option 1	LNSP See note above
StreetSuffix	Records street suffixes. This value must correspond to a valid Street Suffix Code, reference AS4590.	Address Option 1	LNSP See note above
StreetType	Records the street type abbreviation. This value must correspond to a valid Street Type Code, reference AS4590.	Address Option 1	LNSP See note above
SuburbOrPlaceOrLocality	The full name of the general locality containing the specific address.	MANDATORY	LNSP See note above
LocationDescriptor	A general field to capture various references to address locations alongside another physical location.	Address Option 1	LNSP See note above
PostCode	The descriptor for a postal delivery area, aligned with locality, suburb or place.	MANDATORY	LNSP See note above
StateOrTerritory	Defined State or Territory abbreviation.	MANDATORY	LNSP See note above
DeliveryPointIdentifier	Delivery point identifier - the numeric descriptor for a postal delivery point which is equal to a physical address. The values are in the range 10000000 – 99999999.	OPTIONAL	LNSP See note above
AddressLine	To provide the unstructured address (line 1) where a structured address cannot be supplied.	Address Option 2	LNSP See note above
AddressLine	To provide the unstructured address (line 2) where a structured address cannot be supplied.	Address Option 2	LNSP See note above
AddressLine	To provide the unstructured address (line 3) where a structured address cannot be supplied.	Address Option 2	LNSP See note above
Aggregate	This flag determines whether the energy at this <i>connection point</i> is to be treated as consumer <i>load</i> or as a <i>generating unit</i> (this may include <i>generator</i> auxiliary loads). MSATS will initially set this field to "Y" This value must correspond to a valid Aggregate value in the Aggregate Codes reference table listed in section 1149 .	OPTIONAL	(Defaults to 'Y', AEMO updates to 'N' as required)
FromDate	Start date of the NMI Data record. This indicates the date on which the parameters of this particular NMI data record apply from. The data applies from the beginning of this date (the start of the day, i.e. 00:00).	MANDATORY	LNSP See note above

ToDate	End date of the record. This indicates the date on which the parameters of this particular record end. The data applies until the end of this date (the end of the day, i.e. 23:59). A default date of 9999-12-31 is recorded if EndDate is not provided.	MANDATORY (Defaults to high date unless supplied)	System generated unless supplied.
RowStatus	Indicates whether the record is active or inactive. Whenever a new record is created, it will be A (Active). When, because there has been a change to the data, this record becomes redundant, its MaintActFlg is changed to I (Inactive).	MANDATORY	System generated
MaintenanceDate	Date and time the record was updated. A default date of 9999-12-31 is used when the record is created initially. If the record is subsequently updated, its MaintUpdDt is changed to the date and time the record was updated.	MANDATORY	System generated
CreationDate	Date and time the record was created.	MANDATORY	System generated
Feeder Class	A code to provide Participants with information to indicate the appropriate service level timeframes for performing work in relation to Service Order Requests.	OPTIONAL	LNSP See note above
Customer Classification Code	A code that defines the consumer class as defined in the National Energy Retail Regulations, or in overriding Jurisdictional instruments	MANDATORY	Current FRMP
Customer Classification Threshold Code	A code that defines the consumption threshold as defined in the National Energy Retail Regulations, or in overriding Jurisdictional instruments.	MANDATORY	LNSP See note above

7.8. CATS_NMI_DATA_STREAM

The CATS_NMI_Data_Stream table is a NMI master table containing data that is stored at the *NMI* Datastream level. Information stored at this level includes suffixes, profile name, average daily load etc. It is updated whenever a Change Request containing inbound Datastream data is completed.

Note: Data is only required for this table if the *NMI* is active in the NEM or is used for profile peel-off in accordance with the Metrology Procedure.

Note: References to 'LNSP' includes the ENM for *child connection points*.

Table 7 CATS_NMI_DATA_STREAM

Data Element Name	Description	Standing Data Required	Party to Provide Required To Source
NMI	<i>NMI</i>	MANDATORY See Note.	MDP LNSP
ElectricityDataStream /Suffix	Metering Datastream identifier (for MDM). Identifies the Datastream as delivered to AEMO for settlements purposes. The value must be a valid suffix for this <i>NMI</i> and is active for this date range. The value must comply with requirements of the MSATSNMI Procedures - National Metering Identifier Procedure (NMI) (Document No. ME-GN0590) . If the MeterInstallCode is COMMSn, MRIM, MRAM, VICAM or UMCP, the Suffix value must be in the form Nx where	MANDATORY See Note.	MDP

Formatted: Caption Table

	DataStreamType is I or P for an interval Datastream. If the MeterInstallCode is BASIC, the Suffix value must be numeric.		
ElectricityDataStream /Status	Code used to indicate the status of the suffix. This value must correspond to a valid StreamStatusCode in the Stream Status Codes reference table listed in section 1140.	MANDATORY See Note.	MDP
AveragedDailyLoad	The electrical energy delivered through a <i>connection point</i> or <i>metering point</i> over an extended period normalised to a "per day" basis (kWh).	MANDATORY See Note.	MDP
DataStreamType	Indicates the type of data that the the ElectricityDataStream / Suffix is recording Datastream will report includes interval and basic. Profile data <i>meters</i> are: 1. For registering sample <i>meters</i> used for the calculation of profile shapes where the NMI and Datastream are not used for <i>settlements</i> . 2. For providing external profile shapes into MDM (external PPS). This value must correspond to a valid DataStreamType <i>value</i> in the Data Stream Type Codes reference table listed in section 1140.	MANDATORY See Note.	MDP
ProfileName	The Profile Name is a code that identifies the name of the algorithmically derived shape that is used to allocate a Datastream's consumption to trading intervalsTIs . This value must correspond to a valid code in the MDM-PROFILE table. For all Interval Meters and profile-sample meters , this must be set to 'NOPROF'. For basic-Accumulation Meters, refer to the MDM Profile for valid profile names. <ul style="list-style-type: none"> In Victoria and the ACT, ProfileName must be NSLP. In NSW, QLD and SA, ProfileName must be NSLP or the relevant controlled load profile. This value must correspond to a valid ProfileName value in the Profile Codes reference table listed in section 1140.	MANDATORY See Note.	MDP
FromDate	Start date of the <i>NMI</i> data record. This indicates the date on which the parameters of this particular <i>NMI</i> data record apply from. The data applies from the beginning of this date (the start of the day, i.e. 00:00).	MANDATORY	Party sending transaction
ToDate	End date of the record. This indicates the date on which the parameters of this particular record end. The data applies until the end of this date (the end of the day, i.e. 23:59). A default date of 9999-12-31 is recorded if EndDate is not provided.	MANDATORY (Defaults to high date unless supplied)	System generated unless supplied.
RowStatus	Indicates whether the record is active or inactive. Whenever a new record is created, it will be A (Active). When, because there has been a change to the data, this record becomes redundant, its MaintActFlg is changed to I (Inactive).	MANDATORY	System generated
MaintenanceDate	Date and time the record was updated. A default date of 9999-12-31 is used when the record is created initially. If the record is subsequently updated, its MaintUpdtDt is changed to the date and time the record was updated.	MANDATORY	System generated



CreationDate	Date and time the record was created.	MANDATORY	System generated
--------------	---------------------------------------	-----------	------------------

8.9. CATS_REGISTER_IDENTIFIER

The CATS_Register_Identifier table ~~is a NMI master table~~ contains data that is stored at the register identifier level. Information stored at this level includes the Network Tariff Code. It is updated whenever a Change Request containing inbound register identifier data is completed.

Note: References to "LNSP" includes the ENM for child connection points.

Table 8 CATS_REGISTER_IDENTIFIER

Data Element Name	Description	Standing Data Required	Party to Provide Required To Source	Rules-Schedule 7.5NER Reference / Description
NMI	National Metering Identifier issued by the LNSP in accordance with the NMI Procedure. This number is unique for each <i>connection point</i> within the NEM.	MANDATORY	LNSP	Metering installation identification name S7.5.2(b)(2)
SerialNumber	The Meter Serial number-ID uniquely identifies a <i>meter</i> for a given <i>NMI</i> . Maximum 12 Characters (alpha numeric). Unique for <i>NMI</i> . Use dummy for UMCP (Type 7) and logical (<i>meters</i>). Except for UMCP and logical, MeterSerial should be displayed on physical device also known as property number). SerialNumber to be property number if exists, otherwise the <i>meter</i> manufacturers' serial number, otherwise dummy number.	MANDATORY	Metering Provider "B"MPB	Meter Serial numbersIDs S7.5.2(b)(1)
RegisterID	The RegisterID is used to identify a data source that is obtained from the <i>meter</i> . A single <i>meter</i> may provide multiple data sources.	MANDATORY	MPB Metering Provider "B"	
NetworkTariffCode	The Network Tariff Code is a free text field required by the CATS rules . The text must match the Network Tariff Codes supplied and published by the LNSP. Must be a valid code in from the CATS_Network_Tariff_Codes table.	REQUIRED MANDATORY	MPB Metering Provider "B" LNSP on update	

Formatted: Caption Table, Space Before: 0 pt

Formatted Table

Formatted: Justified, Space Before: 2 pt, After: 2 pt, Line spacing: At least 10 pt, Don't keep with next

STANDING DATA FOR MSATS



NetworkAdditional Information	Free text field.	OPTIONAL	MPBMetering Provider "B"	
UnitOfMeasure	Code to identify the UOM-unit of measure for data held in this register.	MANDATORY	MPBMetering Provider "B"	Data register coding details S7.5.2(b)(10)
TimeOfDay	Code to identify the time validity of register contents. As published by each LNSP.	MANDATORY	MPBMetering Provider "B"	Data register coding details S7.5.2(b)(10)
Multiplier	Multiplier required to take a register value and turn it into a value representing billable energy	MANDATORY	MPBMetering Provider "B"	Summation scheme values and multipliers S7.5.2(b)(9)
DialFormat	Describes the register display format. First number is the number of digits to the left of the decimal place, and the second number is the number of digits to the right of the decimal place.	MANDATORY	MPBMetering Provider "B"	Data register coding details S7.5.2(b)(10)
Suffix	<p>Metering Datastream identifier (for MDM). Identifies each Datastream at the measurement element level for the <i>connection point</i> identified by the <i>NMI</i>.</p> <p>The value must be a valid suffix for this <i>NMI</i> and is active for this date range. The value must match the value provided in the MDFF File.</p> <p>The Suffix value must be unique for each <i>meter</i>.</p> <p>The value must comply with requirements of MSATS the NMI Procedures National Metering Identifier Procedure (NMI) (Document No. ME_GN0590.</p> <p>For interval data streams, the suffix will indicate the individual data streams contributing to the Nx-Suffix value in the CATS_NMI_DataStream table where DataStreamType is I or P.</p> <p>For basic data streams the value will be identical to the related Suffix value in the CATS_NMI_DataStream table.</p>	MANDATORY OPTIONAL	MPBMetering Provider "B"	

STANDING DATA FOR MSATS



ControlledLoad	Indicates whether the <i>energy</i> recorded by this register is created under a Controlled Load regime ControlledLoad field will have "No" if register does not relate to a Controlled Load. If the register relates to a Controlled Load, it should contain a description of the Controlled Load regime.	MANDATORY	MPB Metering Provider "B"	
RegisterDetail/Status	Lookup code to indicate if register is active. Must ensure that RegisterDetail/Status is not Current (C) when ElectricityMeter/Status is Removed (R). This value must correspond to a valid RegisterDetail/Status in from the Meter and RegisterID Codes reference table listed in section 1140 .	MANDATORY	MPB Metering Provider "B"	
ConsumptionType	Actual/Subtractive Indicator. Actual (A) implies volume of energy actually metered between two dates. Cumulative (C) indicates a Meter Reading for a specific date. A second Meter Reading is required to determine the consumption between those two Meter Reading dates. For an Interval Meter, ActCumInd = A. This value must correspond to a valid ConsumptionType in from the Consumption Type Codes reference table listed in section 1140 .	MANDATORY	MPB Metering Provider "B"	
Demand1	This field contains the peak demand value for summer for network Tariff purposes. Units in kW or kVA	OPTIONAL	MPB Metering Provider "B" (Refers to Network Tariff Code)	
Demand2	This field contains an additional demand value (not Summer period). Units in kW or kVA	OPTIONAL	MPB Metering Provider "B" (Refers to Network Tariff Code)	

STANDING DATA FOR MSATS



FromDate	Start date of the <i>NMI</i> data record. This indicates the date on which the parameters of this particular <i>NMI</i> data record apply from. The data applies from the beginning of this date (the start of the day, i.e. 00:00).	MANDATORY	Participant sending transaction	
ToDate	End date of the record. This indicates the date on which the parameters of this particular record end. The data applies until the end of this date (the end of the day, i.e. 23:59). A default date of 9999-12-31 is recorded if EndDate is not provided.	MANDATORY (Defaults to high date unless supplied)	System generated unless supplied.	
RowStatus	Indicates whether the record is active or inactive. Whenever a new record is created, it will be A (Active). When, because there has been a change to the data, this record becomes redundant, its MaintActFlg is changed to I (Inactive).	MANDATORY	System generated	
MaintenanceDate	Date and time the record was updated. A default date of 9999-12-31 is used when the record is created initially. If the record is subsequently updated, its MaintUpdtDt is changed to the date and time the record was updated.	MANDATORY	System generated	
CreationDate	Date and time the record was created.	MANDATORY	System generated	

9-10. CATS_NMI PARTICIPANT RELATIONS

The CATS_NMI_Participant_Relations table is a NMI master table containing data that stores the Roles [that](#) Participants play for each NMI. It is updated whenever a Change Request containing inbound Roles is completed. Each Role record, which contains a single Role code and a single Participant ID, has a start date and an end date, as well as information about when it was created and when it became inactive if it is no longer an active record.

Note: References to 'LNSP' includes the ENM for *child connection points*.

Table 9 CATS_NMI PARTICIPANT RELATIONS

Data Element Name	Description	Standing Data Required	Party to Provide/Required To Source
Party	The Participant ID whose relationship (Role) with the NMI is defined in this table.	MANDATORY	LNSP
NMI	National Metering Identifier issued by the LNSP in accordance with the NMI Procedure. This number is unique for each <i>connection point within the NEM</i> .	MANDATORY	LNSP
Role	This defines the relationship (Role) of the Participant with the NMI in this table.	MANDATORY	LNSP
FromDate	Start date of the NMI-Participant-Relations record. This indicates the date on which the parameters of this particular record apply from. The data applies from the beginning of this date (the start of the day, i.e. 00:00).	MANDATORY	Party sending transaction
ToDate	End date of the record. This indicates the date on which the parameters of this particular record end. The data applies until the end of this date (the end of the day, i.e. 23:59). A default date of 9999-12-31 is recorded if EndDate is not provided.	MANDATORY (Defaults to high date unless supplied)	System generated unless supplied.
RowStatus	Indicates whether the record is active or inactive. Whenever a new record is created, it will be A (Active). When, because there has been a change to the data, this record becomes redundant, its MaintActFlg is changed to I (Inactive).	MANDATORY	System generated
MaintenanceDate	Date and time the record was updated. A default date of 9999-12-31 is used when the record is created initially. If the record is subsequently updated, its MaintUpdtDt is changed to the date and time the record was updated.	MANDATORY	System generated
CreationDate	Date and time the record was created.	MANDATORY	System generated

10.11. REFERENCE TABLES

Table 10 - Valid Aggregate Codes

Aggregate	Description
Y	Customer load
N	Registered Generator NMI

Table 11 - Valid Consumption Type Codes

Consumptiontype	Description
A	Actual Consumption
C	Cumulative Consumption

Table 12 - Valid Data Stream Type Codes

Datastreamtype	Description
I	Interval
C	Basic
P	Profile Data
1	Non-Market Active Import
2	Non-Market Active
3	Non-Market Reactive Import
4	Non-Market Reactive

Table 4 - Valid Jurisdiction Codes

JurisdictionCode	Description
ACT	Australian Capital Territory
NEM	National Electricity Market
NSW	New South Wales
QLD	Queensland
SA	South Australia
VIC	Victoria
TAS	Tasmania

Table 5 - Valid Meter Installation Codes

InstallationTypeCode	Description
BASIC	Basic Consumption Accumulation Meter — Type 6
COMMS1	Interval Meter with communications — Type 1
COMMS2	Interval Meter with communications — Type 2
COMMS3	Interval Meter with communications — Type 3
COMMS4	Interval Meter with communications — Type 4
MRIM	Manually Read Interval Meter — Type 5
UMCP	Unmetered Supply — Type 7

Formatted: No bullets or numbering

Formatted: No bullets or numbering

InstallationTypeCode	Description
PROF	Profile Setup
SAMPLE	Sample Meter

Table 6 — Valid NMI Class Codes

NmiClassificationCode	Description
LARGE	Large
GENERATR	Generator
WHOLESALE	Wholesale
EPROFILE	External Profile Shape
SAMPLE	Sample Meter
INTERCON	Interconnector
SMALL	Small (Defined by jurisdictions — generally less than 160MWh per annum consumption)

Table 7 — Table 7 - Valid NMI Status Codes

MasterData/Status	Description
D	Not Energised (De-energised)
X	Extinct NMI
A	Active NMI
G	Green Field Site NMI

Table 8 Table 13 Table 8 - Valid Profile Codes

ProfileName	Description
NSLP	Net System Load Profile. The profile is calculated by MSATS. NSLP represents the system load after all actual <i>interval metering data</i> or specified previously-calculated profiled <i>metering data</i> that is not dependent on the NSLP has been subtracted from a known total system load and represents system-wide usage by consumption-type <i>metering installations</i> .
CLOADNSWCE	Controlled Load profile: Country Energy. (Now Essential Energy) Profile Names beginning with CLOAD are Controlled Load profiles. Controlled Load profiles are applied to Controlled Load Datastreams in NSW. There is one Controlled Load profile for each LNSP area. The names all begin with CLOADNSW to indicate that they are NSW Profile Names followed by two characters to indicate the LNSP area to which it belongs (e.g. EA = EnergyAustralia).
CLOADNSWEA	Controlled Load profile: EnergyAustralia (Now Ausgrid).
CLOADNSWIE	Controlled Load profile: IntegralEnergy (Now Endeavour Energy)
QLDEGXCL31	Controlled Load profile Energex tariff 31
QLDEGXCL33	Controlled Load profile Energex tariff 33
SACLOAD	South Australian Controlled Load.
NOPROF	Used for interval Datastream types (to indicate that such Datastreams do not need to be profiled to obtain 'readings' for each <i>settlements</i> interval because the data is supplied in 30-minute intervals).

Table 9 — Table 9 – Valid Stream Status Codes

ElectricityDataStream/Status	Description
I	Inactive MDM Datastream
A	Active MDM Datastream

Note: Refer to the MSATS CATS Procedure section 4 for details on the valid codes for the following:

- Jurisdiction Codes
- Metering Installation Type Codes
- NMI Classification Codes
- NMI Status Codes
- Datastream Status Codes

Formatted: Font: Not Bold

Formatted: Bulleted + Level: 1 + Aligned at: 0.63 cm +
Indent at: 1.27 cm

14.12. USE OF NMI SUFFIX TO POPULATE CATS_REGISTER_IDENTIFIER

For any particular *connection point* there may be multiple energy measurement elements and data recorders with multiple channels. Accurate identification of Datastreams is essential. The NMI Procedure includes the requirements for the use of a suffix to the *NMI* that identifies these Datastreams. The DataStreamSuffix detailed in the NMI Procedure provides identification at the measurement element level for all Datastreams comprising from the *connection point* identified by the *NMI*. The DataStreamSuffix is commonly known as the NMISuffix. The NMISuffix is labelled as 'Suffix' in the Browser and is the ElectricityDataStream/Suffix data element in aseXML.

The NMISuffix was first used in the NMI Procedure to describe, in conjunction with the *NMI*, the data transferred from the MDP to AEMO and Participants for *settlements of market energy*. The NMISuffix was further extended to describe Datastreams in MSATS, and numeric suffixes were developed to describe the data from type 6 *metering installations*.

In MSATS, the NMISuffix is used in the CATS_NMI_DATA_STREAM table to describe the data as delivered to AEMO. For *settlements* purposes this data must be 'NET' [Export from *network*, less import to *network*] and will be 'Nx' for an interval Datastream, or numeric for an Accumulation Meter.

In MSATS release 2.0 a new table, CATS_REGISTER_IDENTIFIER, was introduced to link identifiers for the source *meter* register(s) to the Datastream suffix in the CATS_NMI_DATA_STREAM table. The purpose of the table is to enable the alignment of the data held in MSATS and the data being transferred between Participants in the B2B process.

This link is achieved through the RegisterID (which describes the data source at the *metering installation*) and ElectricityDataStream/Suffix (which describes the NMISuffix to which the RegisterID contributes) data elements. This is a many-to-one relationship, i.e. there may be multiple RegisterID values for each ElectricityDataStream/Suffix value in the CATS_REGISTER_IDENTIFIER table.

- The RegisterID identifies the measurement element and type of measurement for an Interval Meter, and identifies the location of a stored energy value in an Accumulation Meter.
- The ElectricityDataStream/Suffix value in the CATS_NMI_DATA_STREAM table identifies the Datastream registered in MSATS. For *settlements* purposes, Interval Meter Datastreams will be the NET suffix (format Nx) and for Accumulation Meter Datastreams the suffix value is numeric. MSATS requires data to be delivered against this suffix (if the Datastream is ACTIVE). MSATS does not validate the values entered in this field.
- The ElectricityDataStream/Suffix value in the CATS_REGISTER_IDENTIFIER table identifies the individual Datastream(s) contributing to the ElectricityDataStream/Suffix value in the CATS_NMI_DATA_STREAM table. For interval Datastreams, the suffix(es) will indicate the individual Datastream(s) contributing to the Nx Suffix value in the CATS_NMI_DATA_STREAM table where the DataStreamType is P or I (Refer section 14.13 for examples). For accumulation Datastreams the value will be numeric and will be identical to the related Suffix value in the CATS_NMI_DATA_STREAM table (refer section 13.12 for examples).

- The ElectricityDataStream/Suffix values used in the CATS_REGISTER_IDENTIFIER table are used to identify *metering data* contained in MDFF Files (in the NMISuffix field).
- The linkage between the RegisterID and ElectricityDataStream/Suffix exists because can only occur if the ElectricityDataStream/Suffix data element is populated in the CATS_REGISTER_IDENTIFIER table. As this data element is Optional in this table, the linkage is reliant on action by the MPB to manage and provide this data.
- The RegisterID data element has no standard format; therefore, the MPB must determine the appropriate population of this field, e.g. it may be used to indicate the programming code of the register.

There is an inconsistent understanding across industry of the meaning of the terms 'register' and 'datastream'. Conventionally, to field metering personnel, a 'register' contains a single value, while a 'datastream' represents an array of time separated register values in chronological order.

For Accumulation Meters, the RegisterID refers to the non-volatile storage of the cumulative energy register(s). The RegisterID will have identification with the displays of the *meters*, or identification of internal data stores.

For Accumulation Meters, the ElectricityDataStream/Suffix data element in the CATS_REGISTER_IDENTIFIER table may have a many-to-one relationship with the ElectricityDataStream/Suffix data element in the CATS_NMI_DATA_STREAM table. That is, the same Suffix may occur several times in the CATS_REGISTER_IDENTIFIER table and occur once only in the CATS_NMI_DATA_STREAM table.

For Interval Meters, the definition of the RegisterID field is less obvious. To make this field useful, the RegisterID should be associated with the ElectricityDataStream/Suffix. As Interval Meters may have multiple measurement elements and there may be multiple *meters* for a *NMI*, the MDP must manage Datastreams against a *NMI* to avoid duplication of ElectricityDataStream/Suffixes and provide correct mapping of RegisterIDs.

42.13. ASSIGNMENT OF DATA – BASIC ACCUMULATION METERS

This section details examples of the assignment of data for various basic *metering installations*. For basic Accumulation Meters, the Suffix values in CATS_RegisterREGISTER_IDENTIFIERidentifier and CATS_NMI_DATAata_STREAMtream tables are always numeric.

42.4.13.1. Single Meter, no controlled load

A Basic Accumulation Meter with a single register measuring a Non-Controlled Load will have a single Datastream suffix 11 defined for the *NMI*.

Table 14 Example CATS_NMI_DATA_STREAM

Data Element:	NMI	Suffix	ElectricityData Stream/Status
Value	0123456789	11	A

The CATS_RegisterREGISTER_IDENTIFIERidentifier table indicates that the *meter* has only one register. The Suffix in the CATS_RegisterREGISTER_IDENTIFIERidentifier 11 denotes that data from RegisterID 01 contributes to the Datastream identified by Suffix 11 in CATS_NMI_DATAata_STREAMtream.

Table 15 Example CATS_REGISTER_IDENTIFIER

Data Element:	Serial Number	RegisterID	UnitOfMeasure	TimeOfDay	Suffix	Controlled Load
Value	ABCD1111	01	KWH	ALLDAY	11	No

The Suffix in CATS_NMI_DATAstream will be recorded as '11' by the Metering-Data ProviderMDP and the Suffix in CATS_REGISTERregister_IDENTIFIERidentifier must then be '11'.

12.2.13.2. Two Single Element Meters, no controlled load

The NMI has two basic-Accumulation Meters, each meter with single register. The data from the two meters will be submitted to MSATS as two Datastreams.

Table 16 Example CATS_NMI_DATA_STREAM

Data Element:	NMI	Suffix	ElectricityData Stream/Status
Values	0123456789	11	A
	0123456789	12	A

Table 17 Example CATS_REGISTER_IDENTIFIER

Data Element:	Serial Number	RegisterID	UnitOfMeasure	TimeOfDay	Suffix	Controlled Load
Values	ABCD1111	01	KWH	ALLDAY	11	No
	XYZA1112	01	KWH	ALLDAY	12	No

12.3.13.3. Two Single Element Meters, one with controlled load

A NMI has two basic-Accumulation Meters, each meter has a single register, and one meter is measuring a Controlled Load. The data from the two meters is submitted to MSATS as two Datastreams.

Table 18 Example CATS_NMI_DATA_STREAM

Data Element:	NMI	Suffix	ElectricityData Stream/Status
Value	0123456789	11	A
	0123456789	42	A

Table 19 Example CATS_REGISTER_IDENTIFIER

Data Element:	Serial Number	RegisterID	UnitOfMeasure	TimeOfDay	Suffix	Controlled Load
Values	ABCD1111	01	KWH	TOTAL	11	No
	XYZA1112	01	KWH	CL1	42	HWLoad

12.4.13.4. One Meter with Two Registers, one measuring a controlled load

NMI has one basic-Accumulation Meter with two registers. The second register is measuring a Controlled Load.

Table 20 Example CATS_NMI_DATA_STREAM

Data Element:	NMI	Suffix	ElectricityData Stream/Status
Values	0123456789	11	A
	0123456789	41	A

Table 17 **Table 21** **Example CATS REGISTER IDENTIFIER**

Data Element:	Serial Number	RegisterID	UnitOfMeasure	TimeOfDay	Suffix	Controlled Load
Value	ABCD1111	01	KWH	PEAK	11	No
	ABCD1111	02	KWH	CL1	41	HWLoad

12.5.13.5. Single Multi-function Meter

[Basic Accumulation](#) Meter has 4 registers, one register being a Controlled Load.

Table 18 **Table 22** **Example CATS NMI DATA STREAM**

Data Element:	NMI	Suffix	ElectricityData Stream/Status
Values	0123456789	11	A
	0123456789	21	I
	0123456789	31	A
	0123456789	41	A

Each register is separately identified in CATS_NMI_Data_Stream. However, register 2 on *meter 1* is inactive in MSATS, and therefore data is not accepted by MSATS for this Suffix.

Table 19 **Table 23** **Example CATS REGISTER IDENTIFIER**

Data Element:	Serial Number	RegisterID	UnitOfMeasure	TimeOfDay	Suffix	Controlled Load
Values	ABCD1111	01	KWH	ALLDAY	11	No
	ABCD1111	02	KWH	NOTUSED	21	No
	ABCD1111	03	KWH	OFFPEAK	31	No
	ABCD1111	04	KWH	CL1	41	HWLoad

Note: The *meter* may have register identification and therefore these numbers can be used in the table as RegisterID.

13.6. Two meters, three registers. One register measures a controlled load

Table 20 **Table 24** **Example CATS NMI DATA STREAM**

Data Element:	NMI	Suffix	ElectricityData Stream/Status
Values	0123456789	11	A
	0123456789	21	A
	0123456789	42	A

Table 24 **Table 25** **Example CATS REGISTER IDENTIFIER**

Data Element:	Serial Number	RegisterID	UnitOfMeasure	TimeOfDay	Suffix	Controlled Load
Values	ABCD1111	01	KWH	PEAK	11	No
	ABCD1111	02	KWH	OFFPEAK	21	No
	XYZA1112	01	KWH	CL1	42	HWLoad

13.14. ASSIGNMENT OF DATA – INTERVAL METERS

This section details examples of the assignment of data for various Interval Meterings installations.

14.1. One meter

Table 22 **Table 26** **Example CATS NMI DATA STREAM**

Data Element:	NMI	Suffix	ElectricityData Stream/Status
Value	0123456789	N1	A

The CATS_Register_Identifier table indicates that the *meter* has only one register. The Suffix in the CATS_REGISTER_IDENTIFIER [E1] denotes that data from RegisterID 01 contributes to the Datastream identified by Suffix N1 in the CATS_NMI_DATA_STREAM table.

Table 27 **Example CATS REGISTER IDENTIFIER**

Data Element:	Serial Number	RegisterID	UnitOfMeasure	TimeOfDay	Suffix
Value	ABCD1111	01	KWH	ALLDAY	E1

E1 indicates that it is a single element measuring export.

13.14.2. Import/Export meter

Interval Meter has a two registers, registering import and export energy. A single Datastream suffix N1 is defined for the NMI indicating a netting-off of export less import Datastreams for this connection point.

Table 23 **Table 28** **Example CATS NMI DATA STREAM** **CATS_Register_Identifier Table for Example**

Data Element:	NMI	Suffix	ElectricityData Stream/Status
Value	0123456789	N1	A

The CATS_Register_Identifier REGISTER_IDENTIFIER table indicates that the *meter* has two registers, one for IMPORT and one for EXPORT.

The Suffixes in the CATS_REGISTER_IDENTIFIER Register_Identifier denote that data from RegisterIDs 'E1' and 'B1' contribute to the Datastream identified by Suffix 'N1' in CATS_NMI_Data_Stream DATA_STREAM. That is, the Datastreams 'E1' and 'B1' supplied by the MDP to the FRMP for this *meter* have contributed to the Datastream N1 in MSATS.

Table 24 **Table 29** **CATS_Register_Identifier Table for Example Example**
CATS REGISTER IDENTIFIER

Data Element:	Serial Number	RegisterID	UnitOfMeasure	TimeOfDay	Suffix
Values	ABCD1111	E1	KWH	ALLDAY	E1
	ABCD1111	B1	KWH	ALLDAY	B1

Only one RegisterID with the Suffix 'E1' permitted per *meter* in CATS_Register_IdentifierREGISTER_IDENTIFIER.

Only one RegisterID with the Suffix 'B1' permitted per *meter* in CATS_Register_IdentifierREGISTER_IDENTIFIER.

The energy volumes for the Suffix 'N1' in CATS_NMI_DATA_STREAMData_Stream are calculated by $N1 = E1 - B1$.

13.2.14.3. One meter: multiple registers

Interval Meter has a single measurement element registering import and export *energy*, reactive and *voltage*. A single Datastream Suffix 'N1' is defined for the *NMI* indicating netting-off of all *energy* Datastreams for this *connection point*.

Table 25Table 30 Example CATS_NMI_DATA_STREAM

Data Element:	NMI	Suffix	ElectricityData Stream/Status
Value	0123456789	N1	A

The CATS_Register_Identifier table indicates that the *meter* has five registers: two for IMPORT of *energy* and reactive; two for EXPORT of *energy* and reactive; and one for *voltage* monitoring. The Suffixes in the CATS_REGISTER_IDENTIFIER [N1] denote that data from RegisterID 'E1' and 'B1' contribute to the Datastream identified by suffix N1 in CATS_NMI_DATA_STREAM.

Table 26Table 31 CATS_Register_Identifier Table for ExampleExample
CATS_REGISTER_IDENTIFIER

Data Element:	Serial Number	RegisterID	UnitOfMeasure	TimeOfDay	Suffix
Values	ABCD1111	E1	KWH	ALLDAY	E1
	ABCD1111	B1	KWH	ALLDAY	B1
	ABCD1111	Q1	KVARH	ALLDAY	Q1
	ABCD1111	K1	KVARH	ALLDAY	K1
	ABCD1111	V1	VOLTS	ALLDAY	V1

The energy supplied-volumes for the Suffixto-MSATS against 'N1' is calculated by NET ($E1 - B1$).

13.3.14.4. One meter: Twin Measurement Elements

Certain multifunction *meters* have the capability for initial installation as an basic-Accumulation Meter, but can be re-programmed to provide *interval metering data*.

The Rules-NER do not permit the use of two different types of *metering installation* on the one *NMI*, and therefore the se interval-and-basictwo *metering* functions MUST NOT be active simultaneously in MSATS. **The MDP and RP will be held accountable for a breach of this requirement.**

The CATS_REGISTER_IDENTIFIERRegister_Identifier can be used to record the *meter* capability.

If this *meter* were configured as an basic-Accumulation Meter in MSATS, the configuration might be as shown in the two-tTables below36 & 37.

Table 27Table 32 Example CATS_NMI_DATA_STREAM

Data Element:	NMI	Suffix	ElectricityData Stream/Status
Values	0123456789	N1	I

Data Element:	NMI	Suffix	ElectricityData Stream/Status
	0123456789	N2	I
	0123456789	11	A
	0123456789	21	A
	0123456789	31	A
	0123456789	41	A

Table 28 **Table 33** **Example CATS REGISTER IDENTIFIER**

Data Element:	Serial Number	RegisterID	UnitOfMeasure	TimeOfDay	Suffix
Values	AB888888	E1	KWH	ALLDAY	null
	AB888888	E2	KWH	ALLDAY	null
	AB888888	25	KWH	PEAK	11
	AB888888	26	KWH	SHOULDER	21
	AB888888	35	KWH	OFFPEAK	31
	AB888888	36	KWH	CL1	41

The CATS_REGISTER_IDENTIFIER table values for this meter when it is operated as an Interval Meter are shown below. The RegisterID for the basic Accumulation Meter registers in this type of meter are user defined. The Interval Meter suffixes must be added to the NMI and made active, and the basic Suffixes made inactive at the same date.

Table 29 **Table 34** **Example CATS NMI DATA STREAMCATS Register Identifier Table for Example**

Data Element:	NMI	Suffix	ElectricityDataStream/Status
Values	0123456789	N1	A
	0123456789	N2	A
	0123456789	11	I
	0123456789	21	I
	0123456789	31	I
	0123456789	41	I

Table 30 **Table 35** **Example CATS REGISTER IDENTIFIER**

Data Element:	Serial Number	RegisterID	UnitOfMeasure	TimeOfDay	Suffix
Values	AB888888	E1	KWH	ALLDAY	E1
	AB888888	E2	KWH	ALLDAY	E2
	AB888888	25	KWH	PEAK	null
	AB888888	26	KWH	OFFPEAK	null
	AB888888	35	KWH	PEAK	null
	AB888888	36	KWH	OFFPEAK	null

If a second *meter* of the same configuration were established on this NMI 'E3' and 'E4' would be required for the Datastreams to provide MDPs and *retailers* with unambiguous identification of Datastreams.

14.15. ASSIGNMENTS OF DATA – SAMPLE METERS

The application of profiles in accordance with the Metrology Procedure requires *interval metering data* from Sites that have [basic-Accumulation](#) Metering. However, the [Rules-NER](#) do not permit different metering installation types on the one NMI, and in any case, the Participants associated with the *interval metering data* are different to those associated with the [basic-Accumulation](#) Meter. Therefore, for these *connection points*, two different NMIs are used.

There are *meters* that can combine the required [basic-Accumulation](#) Metering and Interval Metering [roles/functions](#). An example is shown below.

14.1.15.1. Multifunction Sample Meter

In this case, a single *meter* is registered within MSATS for two purposes against two NMIs. This is a special case, and should not be used other than for this non-standard purpose. The *meter* has two circuits, with [basic-Accumulation](#) Metering for *energy* trading and Interval Metering for the sample profile.

In this example, the NMI 9801234567 is [associated with](#) the sample *meter installation* and NMI 9876543210 [is with](#) the End-User [consumer](#) installation.

Table 34 [Table 36](#) [Example CATS NMI DATA STREAM](#)

Data Element:	NMI	Suffix	ElectricityDataStream/Status	DataStreamType
Values	9801234567	N1	A	P
	9876543210	11	I	C
	9876543210	12	I	C
	9876543210	41	A	C

Table 32 [Table 37](#) [Example CATS REGISTER IDENTIFIER](#)

Data Element:	NMI	MeterSerial	RegisterID	UnitOfMeasure	TimeOfDay	Suffix
Values	9801234567	AB888888	E1	KWH	ALLDAY	E1
	9876543210	AB888888	11	KWH	PEAK	null
	9876543210	AB888888	12	KWH	OFFPEAK	null
	9876543210	AB888888	41	KWH	CL1	41

Note: Suffix '11/12' have a Status of 'I' for 1st Tier and 'A' for 2nd Tier.

First tier *metering data* is not required for AEMO to settle the *market*.

Controlled Load data for first tier and second tier is required by AEMO to settle the *market*.

In the example above, once the End-User's Site [consumer](#) becomes [second-a-tTier 2 Site](#), all three basic Datastreams need to become active (StreamStatusCode = A).

15.16. CROSS REFERENCE OF BROWSER AND ASEXML DATA ELEMENTS

The tables below list the names that are used in the [MSATS bB](#) browser for each of the MSATS tables detailed in sections [43](#) to [109](#). The table also provides the aseXML data element names and the respective formats used in each context.

In some cases, such as date fields, the format of the field is shown differently in the Browser to that used in the related aseXML transactions. Also, aseXML uses full words throughout, rather than the coded values used in the Browser.

Refer section 176 for examples of the typical data element values as shown in the Browser. Section 187 provides definitions of the Browser formats shown in this section.

Table 33 Table 38 CATS_Meter_Register

Browser Field Name	aseXML Data Element Name	aseXML Path	Browser Format	aseXML Data Type
Additional Site Information	AdditionalSiteInformation	ElectricityMeter/AdditionalSiteInformation	VARCHAR2(100)	xsd:string maxLen = 100
Asset Management Plan	AssetManagementPlan	ElectricityMeter/AssetManagementPlan	VARCHAR2(50)	xsd:string maxLen = 50
Calibration Tables	CalibrationTables	ElectricityMeter/CalibrationTables	VARCHAR2(50)	xsd:string maxLen = 50
Communication Equipment Type	CommunicationsEquipmentType	ElectricityMeter/CommunicationsEquipmentType	VARCHAR2(4)	xsd:string maxLen = 4
Communication Protocol	CommunicationsProtocol	ElectricityMeter/CommunicationsProtocol	VARCHAR2(50)	xsd:string maxLen = 50
Data Conversion	DataConversion	ElectricityMeter/DataConversion	VARCHAR2(50)	xsd:string maxLen = 50
Data Validations	DataValidations	ElectricityMeter/DataValidations	VARCHAR2(50)	xsd:string maxLen = 50
Estimation Instruction	EstimationInstructions	ElectricityMeter/EstimationInstructions	VARCHAR2(50)	xsd:string maxLen = 50
Last Test Date	LastTestDate	ElectricityMeter/LastTestDate	dd-mmm-yyyy	xsd:date
Measurement Type	MeasurementType	ElectricityMeter/MeasurementType	VARCHAR2(4)	xsd:string maxLen = 4
Meter Constant	Constant	ElectricityMeter/Constant	VARCHAR2(12)	xsd:string maxLen = 12
Meter Hazard	Hazard	ElectricityMeter/Hazard	VARCHAR2(12)	xsd:string maxLen = 12
Meter Installation Type Code	InstallationTypeCode	ElectricityMeter/InstallationTypeCode	VARCHAR2(8)	xsd:string maxLen = 8
Meter Location	Location	ElectricityMeter/Location	VARCHAR2(50) See AddlSiteInfo (above)	xsd:string maxLen = 50
Meter Manufacturer	Manufacturer	ElectricityMeter/Manufacturer	VARCHAR2(15)	xsd:string maxLen = 15
Meter Model	Model	ElectricityMeter/Model	VARCHAR2(12)	xsd:string maxLen = 12
Meter Point	Point	ElectricityMeter/Point	VARCHAR(2)	xsd:string maxLen = 2
Meter Program	Program	ElectricityMeter/Program	VARCHAR2(30)	xsd:string maxLen = 30
Meter Read Type	ReadTypeCode	ElectricityMeter/ReadTypeCode	VARCHAR(4)	xsd:string maxLen = 4

Meter Route	Route	ElectricityMeter/Route	VARCHAR2(12)	xsd:string maxLen = 12
Meter Serial ID Meter ID (Different on two screens)	SerialNumber	ElectricityMeter/SerialNumber	VARCHAR2(12)	xsd:string maxLen = 12
Status Code	Status	ElectricityMeter/Status	CHAR(1)	xsd:string with enumeration
Meter Use	Use	ElectricityMeter/Use	VARCHAR2(10)	xsd:string maxLen = 10
Next Scheduled Read Date	NextScheduledReadDate	ElectricityMeter/NextScheduledReadDate	dd-mmm-yyyy	xsd:date
Next Test Date	NextTestDate	ElectricityMeter/NextTestDate	dd-mmm-yyyy	xsd:date
NMI	NMI	NMI	CHAR(10)	xsd:string maxLen = 10
Passwords	Password	ElectricityMeter/Password	VARCHAR2(20)	xsd:string maxLen = 20
Remote Phone Number	RemotePhoneNumber	ElectricityMeter/RemotePhone Number	VARCHAR2(12)	xsd:string maxLen = 12
Test & Calibration Program	TestCalibrationProgram	ElectricityMeter/TestCalibration Program	VARCHAR2(50)	xsd:string maxLen = 50
Test Performed By	TestPerformedBy	ElectricityMeter/TestPerformedBy	VARCHAR2(20)	xsd:string maxLen = 20
Test Result Accuracy	TestResultAccuracy	ElectricityMeter/TestResultAccuracy	NUMBER(8,5)	xsd:decimal totdig = 8 fracdig = 5
Test Result Notes	TestResultNotes	ElectricityMeter/TestResultNotes	VARCHAR2(50)	xsd:string maxLen = 50
Transformer Location	TransformerLocation	ElectricityMeter/Transformer Location	VARCHAR2(30)	xsd:string maxLen = 30
Transformer Ratio	TransformerRatio	ElectricityMeter/TransformerRatio	VARCHAR2(20)	xsd:string maxLen = 20
Transformer Type	TransformerType	ElectricityMeter/TransformerType	VARCHAR2(20)	xsd:string maxLen = 20
User Access Rights	UserAccessRights	ElectricityMeter/UserAccessRights	VARCHAR2(50)	xsd:string maxLen = 50
Start Date	FromDate	FromDate	dd-mmm-yyyy	xsd:dateTime
End Date	ToDate	ToDate	dd-mmm-yyyy	xsd:dateTime
Updated On	MaintenanceDate	MaintenanceDate	dd-mmm-yyyy (summary screen) dd-mmm-yyyy hh:mm:ss (detail screen)	xsd:dateTime
Created On	CreationDate	CreationDate	dd-mmm-yyyy (summary screen) dd-mmm-yyyy hh:mm:ss (detail screen)	xsd:dateTime



Activity Status	RowStatus	RowStatus	CHAR(1)	xsd:string with enumeration
-----------------	-----------	-----------	---------	-----------------------------

Table 34 **Table 39** CATS_DLF_Codes

Browser Field Name	aseXML Data Element Name	aseXML Path	Browser Format	aseXML Data Type	Formatted Table
DLF Code	DistributionLossFactorCode	DistributionLossFactorCode	VARCHAR2(4)	xsd:string maxLen = 4	
Description	DistributionLossFactorDescription	DistributionLossFactorDescription	VARCHAR2(50)	xsd:string maxLen = 50	
DLF Value	DistributionLossFactorValue	DistributionLossFactorValue	NUMBER(6,5)	xsd:decimal minIncl = 0 maxIncl = 2 totdig = 6 fracdig = 5	
Jurisdiction	JurisdictionCode	ElectricityStandingData/MasterData/JurisdictionCode	VARCHAR2(3)	xsd:string maxLen = 3	
Activity Status	RowStatus	RowStatus	CHAR(1)	xsd:string with enumeration	
Start Date	FromDate	FromDate	dd-mmm-yyyy	xsd:dateTime	
End Date	ToDate	ToDate	dd-mmm-yyyy	xsd:dateTime	
Updated On	MaintenanceDate	MaintenanceDate	dd-mmm-yyyy (summary screen) dd-mmm-yyyy hh:mm:ss (detail screen)	xsd:dateTime	
	CreationDate	CreationDate	dd-mmm-yyyy (summary screen) dd-mmm-yyyy hh:mm:ss (detail screen)	xsd:dateTime	

Table 35 **Table 40** CATS_Emb_Net_ID_Codes

Browser Field Name	aseXML Data Element Name	aseXML Path	Browser Format	aseXML Data Type	Formatted Table
Code	EmbeddedNetworkIdentifier	EmbeddedNetworkIdentifier	VARCHAR2(10)	xsd:string maxLen = 10	
Description	EmbeddedNetworkDescription	EmbeddedNetworkDescription	VARCHAR2(50)	xsd:string maxLen = 50	
Locality/Suburb	SuburbOrPlaceOrLocality	ElectricityStandingData/MasterData/Address/AustralianAddress/SuburbOrPlaceOrLocality	VARCHAR2(46)	xsd:string maxLen = 46	
Postcode	PostCode	ElectricityStandingData/MasterData/Address/AustralianAddress/PostCode	VARCHAR2(4)	xsd:string pattern: [p{N}]{4}	
State	StateOrTerritory	ElectricityStandingData/MasterData/Address/AustralianAddress/StateOrTerritory	VARCHAR2(3)	xsd:string with enumerations	
Activity Status	RowStatus	RowStatus	CHAR(1)	xsd:string with enumeration	
Start Date	FromDate	FromDate	dd-mmm-yyyy	xsd:dateTime	
End Date	ToDate	ToDate	dd-mmm-yyyy	xsd:dateTime	

Updated On	MaintenanceDate	MaintenanceDate	dd-mmm-yyyy (summary screen) dd-mmm-yyyy hh:mm:ss (detail screen)	xsd:dateTime
	CreationDate	CreationDate	dd-mmm-yyyy (summary screen) dd-mmm-yyyy hh:mm:ss (detail screen)	xsd:dateTime

Table 36Table 41 CATS_NMI_Data

Browser Field Name	aseXML Data Element Name	aseXML Path	Browser Format	aseXML Data Type
NMI	NMI	NMI	CHAR(10)	xsd:string maxLen = 10
NMI Classification Code	NMClassificationCode	ElectricityStandingData/MasterData/NMClassificationCode	VARCHAR2(8)	xsd:string maxLen = 8
Status Code	Status	ElectricityStandingData/MasterData/Status	CHAR(1)	xsd:string maxLen = 1
TNI Code	TransmissionNodeIdentifier	ElectricityStandingData/MasterData/TransmissionNodeIdentifier	VARCHAR2(4)	xsd:string maxLen = 4
Jurisdiction Code	JurisdictionCode	JurisdictionCode	VARCHAR2(3)	xsd:string maxLen = 3
DLF Code	DistributionLossFactorCode	ElectricityStandingData/MasterData/DistributionLossFactorCode	VARCHAR2(4)	xsd:string maxLen = 4
Embedded Network ID (Child)	ChildEmbeddedNetworkIdentifier	ElectricityStandingData/MasterData/ChildEmbeddedNetworkIdentifier	VARCHAR2(10)	xsd:string maxLen = 10
Embedded Network (Parent)	ParentEmbeddedNetworkIdentifier	ElectricityStandingData/MasterData/ParentEmbeddedNetworkIdentifier	VARCHAR2(10)	xsd:string maxLen = 10
Building / Property Name	BuildingOrPropertyName	ElectricityStandingData/MasterData/Address/AustralianAddress/StructuredAddress/BuildingOrPropertyName	VARCHAR2(30)	xsd:string maxLen = 30 x 2
Lot Number	LotNumber	ElectricityStandingData/MasterData/Address/AustralianAddress/StructuredAddress/Lot/LotNumber	VARCHAR2(6)	xsd:string pattern: [p(L)\p(N)\p(P)]s{1,6}
Flat/Unit Number	FlatOrUnitNumber	ElectricityStandingData/MasterData/Address/AustralianAddress/StructuredAddress/FlatOrUnit/FlatOrUnitNumber	VARCHAR2(7)	xsd:string pattern: [p(L)\p(N)\p(P)]s{1,7}
Flat/Unit Type	FlatOrUnitType	ElectricityStandingData/MasterData/Address/AustralianAddress/StructuredAddress/FlatOrUnit/FlatOrUnitType	VARCHAR2(4)	xsd:string with enumerations
Floor/Level Number	FloorOrLevelNumber	ElectricityStandingData/MasterData/Address/AustralianAddress/StructuredAddress/FloorOrLevel/FloorOrLevelNumber	VARCHAR2(5)	xsd:string [p(L)\p(N)\p(P)]s{1,5}

Formatted Table

Floor/Level Type	FloorOrLevelType	ElectricityStandingData/MasterData/Address/AustralianAddress/StructuredAddress/FloorOrLevel/FloorOrLevelType	VARCHAR2(2)	xsd:string with enumerations
House Number	HouseNumber	ElectricityStandingData/MasterData/Address/AustralianAddress/StructuredAddress/House/HouseNumber	NUMBER(5)	xsd:nonNegativeInteger maxIncl = 99999
House Number Suffix	HouseNumberSuffix	ElectricityStandingData/MasterData/Address/AustralianAddress/StructuredAddress/House/HouseNumberSuffix	VARCHAR2(1)	xsd:string pattern: [p{L}\p{N}]{1}
Street Name	StreetName	ElectricityStandingData/MasterData/Address/AustralianAddress/StructuredAddress/Street/StreetName	VARCHAR2(30)	xsd:string pattern: [p{L}\p{N}]s-]{1,30}
Street Name Suffix	StreetSuffix	ElectricityStandingData/MasterData/Address/AustralianAddress/StructuredAddress/Street/StreetSuffix	VARCHAR2(2)	xsd:string with enumerations
Street Type	StreetType	ElectricityStandingData/MasterData/Address/AustralianAddress/StructuredAddress/Street/StreetType	VARCHAR2(4)	xsd:string with enumerations
Suburb/Locality	SuburbOrPlaceOrLocality	ElectricityStandingData/MasterData/Address/AustralianAddress/SuburbOrPlaceOrLocality	VARCHAR2(46)	xsd:string maxLen = 46
Location Descriptor	LocationDescriptor	ElectricityStandingData/MasterData/Address/AustralianAddress/StructuredAddress/LocationDescriptor	VARCHAR2(30)	xsd:string pattern: [p{L}\p{N}\p{P}]s]{1,30}
Postcode	PostCode	ElectricityStandingData/MasterData/Address/AustralianAddress/PostCode	VARCHAR2(4)	xsd:string pattern: [p{N}]{4}
State	StateOrTerritory	ElectricityStandingData/MasterData/Address/AustralianAddress/StateOrTerritory	VARCHAR2(3)	xsd:string with enumerations
DPID	DeliveryPointIdentifier	ElectricityStandingData/MasterData/Address/AustralianAddress/StructuredAddress/DeliveryPointIdentifier	NUMBER(8)	xsd:nonNegativeInteger minIncl = 1000000 maxIncl = 99999999
Unstructured Address	AddressLine	ElectricityStandingData/MasterData/Address/AustralianAddress/UnstructuredAddress/Address/AddressLine	VARCHAR2(80)	xsd:string maxLen = 80 x 3
Aggregate Flag	Aggregate	ElectricityStandingData/MasterData/Aggregate	CHAR(1)	xsd:string with enumeration
Start Date	FromDate	FromDate	dd-mmm-yyyy	xsd:dateTime
End Date	ToDate	ToDate	dd-mmm-yyyy	xsd:dateTime
Updated On	MaintenanceDate	MaintenanceDate	dd-mmm-yyyy (summary screen)	xsd:dateTime

			dd-mmm-yyyy hh:mm:ss (detail screen)	
Created On	CreationDate	CreationDate	dd-mmm-yyyy (summary screen) dd-mmm-yyyy hh:mm:ss (detail screen)	xsd:dateTime
Activity Status	RowStatus	RowStatus	CHAR(1)	xsd:string with enumeration
Feeder Class	Feeder Class	ElectricityStandingData/MasterData/FeederClass	VARCHAR2(15)	xsd:string maxLen = 15
Customer Classification Code	CustomerClassificationCode	ElectricityStandingData/MasterData/CustomerClassificationCode	VARCHAR2(20)	xsd:string maxLen = 20
Customer Classification Threshold Code	CustomerThresholdCode	ElectricityStandingData/MasterData/CustomerThresholdCode	VARCHAR2(20)	xsd:string maxLen = 20
NMI	NMI	NMI	CHAR(10)	xsd:string maxLen = 10
Suffix	Suffix	ElectricityDataStream/Suffix	VARCHAR2(2)	xsd:string maxLen = 2
Status Code	Status	ElectricityDataStream/Status	CHAR(1)	xsd:string maxLen = 1
Average Daily Load	AveragedDailyLoad	ElectricityDataStream/AveragedDailyLoad	NUMBER(10)	xsd:integer
Type	DataStreamType	ElectricityDataStream/DataStreamType	CHAR(1)	xsd:string with enumeration
Profile Name	ProfileName	ElectricityDataStream/ProfileName	VARCHAR2(10)	xsd:string maxLen = 10
Start Date	FromDate	FromDate	dd-mmm-yyyy	xsd:dateTime
End Date	ToDate	ToDate	dd-mmm-yyyy	xsd:dateTime
Updated On	MaintenanceDate	MaintenanceDate	dd-mmm-yyyy (summary screen) dd-mmm-yyyy hh:mm:ss (detail screen)	xsd:dateTime
Created On	CreationDate	CreationDate	dd-mmm-yyyy (summary screen) dd-mmm-yyyy hh:mm:ss (detail screen)	xsd:dateTime
Activity Status	RowStatus	RowStatus	CHAR(1)	xsd:string with enumeration

Table 37 **Table 42** CATS_Register_Identifier

Browser Field Name	aseXML Data Element Name	aseXML Path	Browser Format	aseXML Data Type
NMI	NMI	NMI	CHAR(10)	xsd:string maxLen = 10
Meter Serial ID Meter ID (Different on two screens)	SerialNumber	SerialNumber	VARCHAR2(12)	xsd:string maxLen = 12
Register ID	RegisterID	ElectricityMeterRegisterDetail/ RegisterID	VARCHAR2(10)	xsd:string maxLen = 10
Network Tariff Code	NetworkTariffCode	ElectricityMeterRegisterDetail/ NetworkTariffCode	VARCHAR2(10)	xsd:string maxLen = 10
Network Tariff Additional Information	NetworkAdditional Information	ElectricityMeterRegisterDetail/ NetworkAdditionalInformation	VARCHAR2(4000)	xsd:string
Unit of Measure	UnitOfMeasure	ElectricityMeterRegisterDetail/ UnitOfMeasure	VARCHAR2(5)	xsd:string maxLen = 5
Time of Day	TimeOfDay	ElectricityMeterRegisterDetail/ TimeOfDay	VARCHAR2(10)	xsd:string maxLen = 10
Multiplier	Multiplier	ElectricityMeterRegisterDetail/ Multiplier	Number(13,5)	xsd:decimal
Dial Format	DialFormat	ElectricityMeterRegisterDetail/ DialFormat	Number(4,2)	xsd:decimal minIncl = 0 maxIncl = 99.99 totdig = 4 fracdig = 2
Suffix	Suffix	ElectricityMeterRegisterDetail/ Suffix	VARCHAR2(2)	xsd:string maxLen = 2
Controlled Load	ControlledLoad	ElectricityMeterRegisterDetail/ ControlledLoad	VARCHAR2(100)	xsd:string maxLen = 100
Status Code	Status	ElectricityMeterRegisterDetail/ Status	CHAR(1)	xsd:string with enumeration
Actual/Cumulative Indicator	ConsumptionType	ElectricityMeterRegisterDetail/ ConsumptionType	CHAR(1)	xsd:string with enumeration
Demand 1	Demand1	ElectricityMeterRegisterDetail/ Demand1	Number(8)	xsd:integer totdig = 8
Demand 2	Demand2	ElectricityMeterRegisterDetail/ Demand2	Number(8)	xsd:integer totdig = 8
Start Date	FromDate	FromDate	dd-mmm-yyyy	xsd:dateTime
End Date	ToDate	ToDate	dd-mmm-yyyy	xsd:dateTime
Updated On	MaintenanceDate	MaintenanceDate	dd-mmm-yyyy (summary screen) dd-mmm-yyyy hh:mm:ss (detail screen)	xsd:dateTime
Created On	CreationDate	CreationDate	dd-mmm-yyyy (summary screen)	xsd:dateTime

			dd-mmm-yyyy hh:mm:ss (detail screen)	
Activity Status	RowStatus	RowStatus	CHAR(1)	xsd:string with enumeration

Table 38Table 43 CATS_NMI_Participant_Relations

Browser Field Name	aseXML Data Element Name	aseXML Path	Browser Format	aseXML Data Type
Participant ID	Party	Party	VARCHAR2(10)	xsd:string
NMI	NMI	NMI	CHAR(10)	xsd:string maxLen = 10
Role	Role	Role	VARCHAR2(4)	xsd:string maxLen = 4
Start Date	FromDate	FromDate	dd-mmm-yyyy	xsd:dateTime
End Date	ToDate	ToDate	dd-mmm-yyyy	xsd:dateTime
Updated On	MaintenanceDate	MaintenanceDate	dd-mmm-yyyy (summary screen) dd-mmm-yyyy hh:mm:ss (detail screen)	xsd:dateTime
Created On	CreationDate	CreationDate	dd-mmm-yyyy (summary screen) dd-mmm-yyyy hh:mm:ss (detail screen)	xsd:dateTime
Activity Status	RowStatus	RowStatus	CHAR(1)	xsd:string with enumeration

16-17. EXAMPLES OF TYPICAL FIELD VALUES

This section provides examples of typical sets of data element values associated with different types of *connection points*.

The data shown in each example is as shown in the Browser. This reverses the sequence of the day-month-year communicated via aseXML transactions.

Table 39Table 44 CATS_Meter_Register

Data Element Name (as it appears in XML documents)	Browser Field Name(as it appears in MSATS Browser)	Basic Example	Interval Example	Data Element Name
AdditionalSiteInformation	Additional Site Information	MTR ON SITE AT 17B	Red Rooster	AdditionalSiteInformation
AssetManagementPlan	Asset Management Plan	CITIPOWER METER MANAGEMENT PLAN	PER CE DOC: TYPES 1-4 ASSET MANAGEMENT & TEST PLAN	AssetManagementPlan
CalibrationTables	Calibration Tables	Q		CalibrationTables
CommunicationsEquipmentType	Communication Equipment Type	FACE	96	CommunicationsEquipmentType
CommunicationsProtocol	Communication Protocol	NA	EMAIL MINI GATEWAY S/N SU121 MV90 2 TBD TBD	CommunicationsProtocol
DataConversion	Data Conversion	.0005	.0005	DataConversion
DataValidations	Data Validations	<u>As per Metrology Procedure Part B AS PER AEMO DOC MT-MA1680 (CLAUSE 7, 8, 8.3,11)</u>	<u>As per Metrology Procedure Part B AS PER AEMO DOC MT-MA1680 (CLAUSE 8, 8.1, 9.3)</u>	DataValidations
EstimationInstructions	Estimation Instruction	<u>As per Metrology Procedure Part B AS PER AEMO DOC MT-MA1680 (TYPES -61, 62, 65)</u>	<u>As per Metrology Procedure Part B AS PER AEMO DOC MT-MA1680 (TYPES -14)</u>	EstimationInstructions
LastTestDate	Last Test Date	07-05-2004	07-03-2004	LastTestDate
MeasurementType	Measurement Type	EQ	EQ	MeasurementType
Constant	Meter Constant	40	.5	Constant
Hazard	Meter Hazard		Asbestos	Hazard
InstallationTypeCode	Meter Installation Type Code	BASIC	COMMS4	InstallationTypeCode
Location	Meter Location	ON SUB POLE	BEHIND DOOR	Location
Manufacturer	Meter Manufacturer	EMAIL	EDMI	Manufacturer
Model	Meter Model	Q3	Q4	Model
Point	Meter Point	01	01	Point

Formatted Table

STANDING DATA FOR MSATS



Program	Meter Program	30 - NP 3.2 CT FACE PLATE READ	10- AE CT kVAR 9600	Program
ReadTypeCode	Meter Read Type	MV3	RTD	ReadTypeCode
Route	Meter Route	11618	1305	Route
SerialNumber	Meter _Serial ID_ Meter ID (Different on two screens)	525811	201000299	SerialNumber
Status	Status Code	C	C	Status
Use	Meter Use	REVENUE	REVENUE	Use
NextScheduledReadDate	Next Scheduled Read Date	04-10-2006		NextScheduledReadDate
NextTestDate	Next Test Date	17-05-2004	10-05-2004	NextTestDate
NMI	NMI	1122334455	1122334455	NMI
Password	Passwords	12345	12345	Password
RemotePhoneNumber	Remote Phone Number	FACE READ	0555 825 987	RemotePhoneNumber
TestCalibrationProgram	Test & Calibration Program	AS PER AS/NZ 1284	AS PER AS/NZ 1284	TestCalibrationProgram
TestPerformedBy	Test Performed By	Ron Sargeant	SMU	TestPerformedBy
TestResultAccuracy	Test Result Accuracy	-0.20000	-0.11000	TestResultAccuracy
TestResultNotes	Test Result Notes	CHECK AND RESEAL METER	METER TEST CORRECT	TestResultNotes
TransformerLocation	Transformer Location		REAR OFBUILDING	TransformerLocation
TransformerRatio	Transformer Ratio		1500/5	TransformerRatio
TransformerType	Transformer Type		24 WIRE WOUND	TransformerType
UserAccessRights	User Access Rights	AS PER AS/NZ 1284	MDP ONLY ACCESS	UserAccessRights
FromDate	Start Date	14-03-1990	16-03-2002	FromDate
ToDate	End Date	31-12-9999	18-07-2006	ToDate
MaintenanceDate	Updated On	31-12-999 00:00:00	31-12-999 00:00:00	MaintenanceDate
CreationDate	Created On	19-03-1990 00:01:00	18-03-2002 00:01:00	CreationDate
RowStatus	Activity Status	A	A	RowStatus

Formatted: Left



Table 40 **Table 45** CATS_DLF_Codes

Data Element Name	Browser Field Name	Basic & Interval Example
DistributionLossFactorCode	DLF Code	NHV1
DistributionLossFactorDescription	Description	UMPLP - High Voltage
DistributionLossFactorValue	[The actual DLF value]	1.11111
JurisdictionCode	Jurisdiction Code	SA
RowStatus	Activity Status	A
FromDate	Start Date	01-07-1999
ToDate	End Date	30-06-2000
MaintenanceDate	Updated On	31-05-2000 00:30:27
CreationDate		01-06-1999 00:23:32

Table 46 CATS_Emb_Net_ID_Codes

Formatted: Caption Table

Data Element Name	Browser Field Name	Basic & Basic Example
EmbeddedNetworkIdentifier	Code	SE01008111
EmbeddedNetworkDescription	Description	Kingston-On-Murray Caravan Park
SuburbOrPlaceOrLocality	Suburb / Locality	Kingston-On-Murray
PostCode	Postcode	5331
StateOrTerritory	State	SA
RowStatus	Activity Status	A
FromDate	Start Date	05-04-2003
ToDate	End Date	31-12-9999
MaintenanceDate	Updated On	31-12-9999
CreationDate		01-04-2003 13:23:35

Table 47 CATS_NMI_Data

Formatted: Caption Table

Data Element Name	Browser Field Name	Basic Example	Interval Example
NMI	NMI	122334451	1122334455
NMIClassificationCode	NMI Classification Code	SMALL	LARGE
MasterData/Status	Status Code	A	G
TransmissionNodeIdentifier	TNI Code	NRGE	SBER
JurisdictionCode	Jurisdiction Code	NSW	SA
DistributionLossFactorCode	DLF Code	NRGE	NLV2
ChildEmbeddedNetworkIdentifier	Embedded Network ID (Child)	NS01008111	SE01008111
ParentEmbeddedNetworkIdentifier	Embedded Network (Parent)	NS01008111	SE01008111
BuildingOrPropertyName	Building / Property Name	BP	SHELL
LotNumber	Lot Number	22	23

FlatOrUnitNumber	Flat/Unit Number	1	2
FlatOrUnitType	Flat/Unit Type	U	U
FloorOrLevelNumber	Flat/Unit Number	1	1
FloorOrLevelType	Floor/Level Type	FL	FL
HouseNumber	House Number	6	10
HouseNumberSuffix	House Number Suffix	A	B
StreetName	Street Name	BORIS	DORIS
StreetSuffix	Street Name Suffix	N	W
StreetType	Street Type	DR	ST
SuburbOrPlaceOrLocality	Suburb/Locality	ORANGE	LOXTON
LocationDescriptor	Location Descriptor	CNR FRED ST	SHELL SERVICE STATION
PostCode	Postcode	2211	5333
StateOrTerritory	State	NSW	SA
DeliveryPointIdentifier	DPID	01234567	12345678
AddressLine	Unstructured Address 1	Text	Text
AddressLine	Unstructured Address 2	Text	Text
AddressLine	Unstructured Address 3	Text	Text
Aggregate	Aggregate Flag	Y	Y
FromDate	Start Date	01-06-2004	01-06-2001
ToDate	End Date	31-12-9999	01-01-2003
MaintenanceDate	Updated On	31-12-9999 00:00:00	05-01-2003 00:01:00
CreationDate	Created On	04-01-2004 09:31:00	01-06-2001 00:01:00
RowStatus	Activity Status	A	A
FeederClass	Feeder Class	ERGUD	ERGUD
Customer ClassificationCode	Customer Classification	RESIDENTIAL	BUSINESS
CustomerThresholdCode	Customer Threshold	LOW	HIGH

Table 48 CATS_NMI_Data_Stream

Formatted: Caption Table

Data Element Name	Browser Field Name	Basic Example	Interval Example
NMI	NMI	1100445566	2211335544
ElectricityDataStream/Suffix	Suffix	31	N1
ElectricityDataStream/Status	Status Code	A	A
ElectricityDataStream/AveragedDailyLoad	Average Daily Load	5	800
ElectricityDataStream/DataStreamType	Type	C	I
ElectricityDataStream/ProfileName	Profile Name	NSLP	NOPROF

FromDate	Start Date	31-12-2001	01-06-2005
ToDate	End Date	31-12-9999	31-12-9999
MaintenanceDate	Updated On	02-01-2004 13:27:58	31-12-9999
CreationDate	Created On	19-01-2002 17:15:23	05-06-2005 15:12:20
RowStatus	Activity Status	I	A

Table 49 CATS_Register_Identifier

Formatted: Caption Table

Data Element Name	Browser Field Name	Basic Example	Interval Example
NMI	NMI	1100445566	2211335544
SerialNumber	Meter Serial ID Meter ID (Different on two screens)	000012345	112258
RegisterID	Register ID	1	E1
NetworkTariffCode	Network Tariff Code	BLNB2CO	MB2RI
NetworkAdditionalInformation	Network Tariff Additional Information	General Supply Non TOU Eligible	LV TOU Demand Eligible
UnitOfMeasure	Unit of Measure	KWH	KWH
TimeOfDay	Time of Day	ALLDAY	ALLDAY
Multiplier	Multiplier	1.00000	120.00000
DialFormat	Dial Format	5.00	5.10
Suffix	Suffix	11	E1
ControlledLoad	Controlled Load	HWLoad	No
Status	Status Code	C	C
ConsumptionType	Actual/Cumulative Indicator	C	A
Demand1	Demand 1	0	0
Demand2	Demand 2	0	0
FromDate	Start Date	01-08-2004	01-06-2005
ToDate	End Date	31-12-9999	31-12-9999
MaintenanceDate	Updated On	31-12-9999	31-12-9999
CreationDate	Created On	01-11-2005 22:30:30	05-06-2005 09:09:09
RowStatus	Activity Status	A	A

17-18. DATA TYPE CONVENTIONS

The Browser formats used in section 165 are as defined in the following table.

The value of "x" must be positive and cannot be zero.

For explanation of the aseXML data types shown in section 165 refer

<http://www.w3.org/TR/xmlschema-0/#simpleTypesTable>

Table: Browser FormatsCATS_NMI_Participant_Relations

	Format	Definition
1	CHAR(x)	Indicates a field that can only contain alphanumeric characters and must contain exactly "x" characters. Note that leading and trailing "spaces" are considered significant (i.e. form part of the "x" characters for the field).
2	VARCHAR2(x)	Indicates a character field containing up to "x" characters.
3	NUMBER(x)	Indicates a positive integer (zero or above) up to "x" significant digits long; any leading zeroes are not significant and hence "050" is equivalent to "50".
4	NUMBER(x.y)	Indicates a positive number with up to "x" significant characters to the left of the decimal point and "y" decimal places after the decimal point (trailing zeros are optional). In other words, the maximum length of the field as a whole is "x"+"y"+1 characters (the +1 reserving space for the decimal point).